




## Data Sheet 4540036

**Product:** SmartSwitch Push 10A Plus BLCK  
**EI-number:** 4540036  
**Mat.no:** EKO06999  
**EAN:** 27020160699903  
**Packing:** 1  
**Color:**



**Product description:** SmartSwitch push is a digital switch to control up to 10A of ohmic, inductive or capacitive loads directly on the button or be controlled via the ELKO Smart App. It can also be used to trigger moments or automations set in the ELKO Smart App.

---

**Technical specifications:** Voltage: 230V AC / 50 Hz  
Standby: Max. 0,4W  
Nominal current: 10A,  $\cos\phi=0,6$   
Fuse protection: 16A Circuit breaker  
Frequency band: 2,4 GHz  
Transmission capacity: Max. 2,5 mW  
IP degree: IP20  
Operating temperature: 0°C - 35°C  
Communication protocol: Zigbee 3.0  
Connecting terminals: Screw terminals 2x2,5mm<sup>2</sup> solid or stranded types  
Torque: 0,5Nm  
Extension units: Mechanical single push-buttons (unlimited)  
Electronic overload protection  
Overheating protection  
Short-circuit protection  
Soft start

LED: 200W  
Incandescent lamps: 220W  
230V Halogen lamps: 14-150W  
Electronic transformer: 14-150VA  
Capacitive loads: 10A 140  $\mu$ F  
Energy saving lamps: 200W  
Motor single phase 230V: 1000VA

### ELKO AS


E-mail: [elko@elko.no](mailto:elko@elko.no)  
Internet: [www.elko.no](http://www.elko.no)  
Bank: 6219.05.15880  
Org.no.: NO 911 382 563 MVA

ELKO Front office  
Sandstuveien 68, NO-0680 Oslo  
P.O.Box 6598 Etterstad, NO-0607 Oslo  
Tel.: +47 67 80 73 00  
Fax: +47 67 80 73 01

ELKO Plant  
Sporpind Industriområde, NO-3340 Åmot  
Tel.: +47 32 78 91 00  
Fax: +47 32 78 91 01

Size

## Wiring diagram



### ELKO AS

E-mail: [elko@elko.no](mailto:elko@elko.no)  
Internet: [www.elko.no](http://www.elko.no)  
Bank: 6219.05.15880  
Org.no.: NO 911 382 563 MVA

ELKO Front office  
Sandstuveien 68, NO-0680 Oslo  
P.O.Box 6598 Etterstad, NO-0607 Oslo  
Tel.: +47 67 80 73 00  
Fax: +47 67 80 73 01

ELKO Plant  
Sporpind Industriområde, NO-3340 Åmot  
Tel.: +47 32 78 91 00  
Fax: +47 32 78 91 01