



Saves Your Energy

PRODUKTKORT/FDV

17.9.2018

1/2

KA241.12

Navn: **Rekkeklemme**

12-Pol, 4 mm²



Type: KA241.12

GTIN: 6418677103445

EI-nummer:

Beskrivelse: Terminal block with flat base. Mounting hole Ø 3.5 mm. Terminal screw M 3. Terminal block can be ordered precut to desired number of poles.

On request individual pole positions can be marked with desired markings. To order imprinting please specify the characters on your order. Turret or ledge marking available.



Pakke: 250/15750

Enhet: STK



Teknisk spesifikasjon

UL Cat.No. 241.12-AK

Elektriske verider

CSA 241-12

CSA Merkstrøm 30 A

CSA Nominell spenning 300 V

CSA Tversnitt 18-12 AWG

Rangeringer

Nominell nettspenning 450 V

ETIM 7 EC001284

Mekanisk

Tiltrekningsmoment 0.6 Nm

Dimensjoner

Vekt 32.0 g

Mål l x b x h 117x22,2x15,8

Ledertverrsnitt 4 mm²

Festehullets diameter 3.5 mm

Temperaturer

Høyeste driftstemperatur +100 °C

Funksjoner

Antall poler 12

Materialer

Material Polyamid 6

Ensto Nor AS

Prof. Birkelands vei 26A
Postboks 125, 0614 Oslo
Norway

tel. +47 22 90 44 00
fax +47 22 90 44 65

www.ensto.no



KA241.12

Sertifikater

UIL-fil nummer E103245

ETIM

Drill hole distance centrally	10 mm
Explosion-tested version 'Ex e'	
Connectable conductor cross section fine-strand without cable end sleeve	1.5 ... 4 mm ²
Connectable conductor cross section fine-strand with cable end sleeve	1.5 ... 4 mm ²
Connectable conductor cross section solid-core	1.5 ... 4 mm ²
Connectable conductor cross section multi-wired	1.5 ... 4 mm ²
Rated current I _n	30 A
Nominal rated voltage	450 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	Screw connection
Connection position	Sideways
Number of poles	12
Number of clamp positions per pole	2
Mounting method	Direct mounting
Material insulation body	Thermoplastic
Operation temperature	80 °C
Inflammability class of insulation material acc. with UL94	V2
Width/grid dimension	10 mm
Height at lowest possible mounting height	16 mm
Length	22 mm
Closing plate required	
Colour	White
Transparent	x