



FPT1010PP46

Navn:	Brannklassifisert koblingsboks
	100 x 100 mm, PP, 4 x 1,5-6 mm ² , E90
Type:	FPT1010PP46
GTIN:	6438100180782
El-nummer:	1200123
Beskrivelse:	Brannklassifiserte koblingsbokser er designet for å opprettholde funksjonalitet i 30-90 minutter ved brann
Pakke:	1/8
Enhet:	STK



Teknisk spesifikasjon

Innhold	Enclosure base, cover, cover screw, cover line, fastening plate, screw anchors for wall/ceiling mounting, terminal rail, terminal rail mounting screws, ceramic terminals, PE terminal(s), rubber grommets
---------	--

Elektriske verider

Nominell strøm A	41 A
Nominell isolasjonsspenning	750 V

Rangeringer

Nivå på beskyttelse	IP65
ETIM 7	EC002600

Dimensjoner

Ledertverrsnitt	1,5-6 mm ²
Størrelse	100 x 100 x 53.5 mm

Temperaturer

Omgivelsestemperatur	-25 °C...+40 °C, +35°C (24 h)
----------------------	--------------------------------

Funksjoner

Skruehode	Sporhode
-----------	----------

Materialer

Underdel	Polypropylen
Lokk	Polypropylen
Lokkskruvar	Polykarbonat
Lokketetning	Polyuretan

Farger

Farge	Orange
Color code	RAL2003

Sertifikater



FPT1010PP46

Standarder EN 60670-1:2005, EN 60670-22:2006, EN 60947-7-1:2009, DIN 4102-12

ETIM

Max. conductor cross section	6 mm ²
Equipped with	Support rail
Shape	Square
Mounting method	Wall-/ceiling mounting
For tubediameter	25 mm
Inlet from the rear	x
Length	100 mm
Width	100 mm
Depth	53.5 mm
Tackable	
Number of inlets	10
Type of housing feed-through	Seal membrane
Material	Plastic
Halogen free	x
Surface protection	Untreated
Colour	Orange
Degree of protection (IP)	IP65
Cover	Not transparent
Cover attachment	Screwed
Cover model	Blind cover
Castable	
Casting compound included	
Sealable	x
Rated insulation voltage Ui	750 V
Circuit integrity	E 90
Operation temperature	-25 ... 40 °C
With screening	
Weatherproof	
Explosion-tested version	
For Ex-zone gas	None
For Ex-Zone dust	None