


DPRO 230 F (909 240)


- Surge protection with monitoring device and disconnecter
- Visual operating state (green) and fault indication (red)
- Enhanced safety due to fault-proof Y protective circuit



Figure without obligation



Basic circuit diagram DPRO 230 F



Dimension drawing DPRO 230 F

Adapter with integrated surge protection, mains filter and child lock.

Type	DPRO 230 F
Part No.	909 240
SPD according to EN 61643-11 / IEC 61643-11	type 3 / class III
Nominal voltage (a.c.) (U_N)	230 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) (U_C)	255 V (50 / 60 Hz)
Nominal load current (a.c.) (I_L)	10 A
Voltage drop in percent [$L'/N'-N'/L'$ / $L/N-N/L$] for U_C/I_L (ΔU)	≤ 0.3 %
Nominal discharge current (8/20 μ s) (I_n)	3 kA
Total discharge current (8/20 μ s) [$L+N-PE$] (I_{total})	5 kA
Combination wave (U_{OC})	6 kV
Combination wave [$L+N-PE$] ($U_{OC total}$)	10 kV
Voltage protection level [$L-N$] / [$L/N-PE$] (U_p)	≤ 1250 / ≤ 1500 V
Response time [$L-N$] (t_A)	≤ 25 ns
Response time [$L/N-PE$] (t_A)	≤ 100 ns
Max. mains-side overcurrent protection	B 16 A
Short-circuit withstand capability for max. mains-side overcurrent protection (I_{SCCR})	1 kA _{rms}
Temporary overvoltage (TOV) [$L-N$] (U_T) – Characteristic	335 V / 5 sec. – withstand
Temporary overvoltage (TOV) [$L-N$] (U_T) – Characteristic	440 V / 120 min. – safe failure
Temporary overvoltage (TOV) [$L/N-PE$] (U_T) – Characteristic	335 V / 120 min. – withstand
Temporary overvoltage (TOV) [$L/N-PE$] (U_T) – Characteristic	440 V / 5 sec. – withstand
Temporary overvoltage (TOV) [$L+N-PE$] (U_T) – Characteristic	1200 V + U_{REF} / 200 ms – safe failure
Fault indication	red light
Operating state indication	green light
Number of ports	2
Operating temperature range (T_U)	-25 °C ... +40 °C
For mounting on	earthed socket outlets DIN 49440 / DIN 49441
Enclosure material	thermoplastic, pure white, UL 94 V-2
Place of installation	indoor installation
Degree of protection	IP 20
Dimensions	126 x 69 x 41 mm
Mains filter	acc. to EN 60939-1 (DIN VDE 0565-3)
Attenuation for f = 1 MHz, balanced	≥ 40 dB
Attenuation for f = 1 MHz, unbalanced	≥ 30 dB
Weight	194 g
Customs tariff number	85363010
GTIN	4013364117693
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.