







CU-DIN DIM 4-CH 1.5A KNX

Item number EC10430312



The actuators in the DIN Rail series convert digital telegram commands in bus systems into switching and setting actions. This enables the components in the building, such as the lighting, blinds, heating and ventilation, to be controlled conveniently.



Device category	Actuator
Installation type	DIN rail
Installation position	Switching cabinet
Protection type	IP20
Dimensions	Length 90 mm x Width 216 mm x Height/Depth 65 mm
Permissible ambient temperature	-5 °C+45 °C
Warranty	3-year





OTHER PRODUCTS





Solutions

Offices

Education

Health Care Innovations

Demand-driven Automation

Intelligent Lighting

Human Centric Lighting

Light control with DALI-2

Service	
Downloads	
(nowledge	
Support	
ESYLUX Services Company	
/ision and mission	
Experience and quality	
Corporate responsibility	
Research and development	
Cooperations and nemberships	
Awards and prizes	
References lighlights	
ESYLUX Light Control	
DEFENSOR	
COMPACT	
ESY-Pen	
ALVA	
PLAT	
SABELLE	
mprint	
Privacy policy	
Privacy settings Seneral terms and conditions	
Guarantee	
Disclaimer Contact	
2021 ESYLUX GmbH	☐ f ☐ in <