

BRIGHTNESS CONTROLLER

FLAT MINI

Home | Indoor automation | Brightness controller | FLAT MINI



LS FLAT mini KNX

Item number ED10429002



Offers special product features like

- + Daylight dependent constant lighting control, orientation light function, twilight switch function

SHORTFACTS

TECHNICAL DATA

DOWNLOADS

Device category	Brightness controller
Installation type	Recessed mounting
Installation position	Ceiling
Protection type	IP55
Dimensions	Height/Depth 48 mm, Ø 33 mm
Permissible ambient temperature	0 °C...+35 °C
Warranty	5 years

ACCESSORIES

ADAPTER



COMPACT MINI SPOTLIGHT ADAPTER 51/25

Item number EP10426391

Adapter for COMPACT MINI (8 m and 12 m) series for installing motion and presence detectors in spotlights (illuminant size QR-CBC51-Ø 51 mm) with retaining ring



CATALOGUE 2020/2021



CONTACT US

Salutation 

Firstname *

Lastname *

Company *

Phone

E-mail-address *

Subject *

Your message *

- Yes, I agree that ESYLUX will inform me about news in the future via newsletter.
- I have read and agreed to the [privacy policy](#) *

* Required



OTHER PRODUCTS

FLAT MINI
PRESENCE AND MOTION DETECTORS



COMPACT
PRESENCE AND MOTION DETECTORS



PROTECTOR
SMOKE ALARM



SLA
EMERGENCY LIGHTS



ELLEN
WALL AND CEILING LIGHTS



SLP
EMERGENCY LIGHTS





Solutions

Offices

Education

Health Care

Innovations

Demand-driven Automation

Intelligent Lighting

Human Centric Lighting

Light control with DALI-2

Service

Downloads

Knowledge

Support

ESYLUX Services

Company

Vision and mission

Experience and quality

Corporate responsibility

Research and development

Cooperations and
memberships

Awards and prizes

References

Highlights

ESYLUX Light Control

DEFENSOR

COMPACT

ESY-Pen

ALVA

FLAT

ISABELLE

Imprint |
Privacy policy |
Privacy settings |
General terms and conditions |
Guarantee |
Disclaimer |
Contact |
©2021 ESYLUX GmbH

