

SPOTLIGHTS

OS

Home | Outdoor lighting | Spotlights | OS | 5000 K / 9 W



OS 80 LED SPOT 5K WH

Item number EL10523113



Whether they are used to illuminate façades, paths or signs with a high-precision or wide-angle beam, these high-quality OS LED spotlights set the right tone wherever they feature. The designer lamp heads with twin axes can be freely rotated and positioned as required.

SHORTFACTS

TECHNICAL DATA

DOWNLOADS

LIGHT CALCULATION

Device category	Spotlight
Installation type	Surface mounting
Installation position	Wall
Protection type	IP44/lamp head IP65
Dimensions	Length 267 mm x Width 153 mm x Height/Depth 99 mm
Diffusor	transparent
Luminous efficacy	43 lm/W
Luminous flux	394 lm
Rated output P	9 W
Colour temperature	5000 K
Permissible ambient temperature	-25 °C...+50 °C

Warranty

3-year

CATALOGUE 2020/2021



CONTACT US

Salutation 

Firstname *

Lastname *

Company *

Phone

E-mail-address *

Subject *

Your message *

Yes, I agree that ESYLUX will inform me about news in the future via newsletter.

I have read and agreed to the [privacy policy](#) *

* Required



OTHER PRODUCTS

ALVA
UP-/DOWNLIGHTS



BASIC OFL/AFL
FLOODLIGHTS



OFR/AFR
FLOODLIGHTS



MD-W
MOTION DETECTORS



DEFENSOR
TWILIGHT SWITCH



MD
MOTION DETECTORS





Solutions

Offices

Education

Health Care

Innovations

Demand-driven Automation

Intelligent Lighting

Human Centric Lighting

Light control with DALI-2

Service

Downloads

Knowledge

Support

ESYLUX Services

Company

Vision and mission

Experience and quality

Corporate responsibility

Research and development

Cooperations and
memberships

Awards and prizes

References

Highlights

ESYLUX Light Control

DEFENSOR

COMPACT

ESY-Pen

ALVA

FLAT

ISABELLE

Imprint
Privacy policy
Privacy settings
General terms and conditions
Guarantee
Disclaimer
Contact
© 2021 ESYLUX GmbH

