SUN OFL/AFL

1 Outdoor lighting | Floodlights | SUN OFL/AFL | 5000 K / 10 W

•

SUN OFL TR 1000 850 BK


Item number EL10810060

Offers special product features like

+ Overvoltage protection up to 2.5 kV



Device category		Floodlights
Product information		The floodlights are intended for use outdoors. If used inside (e.g. below the ceiling) the heat cannot be sufficiently discharged where necessary.
Installation type	\wedge	Surface mounting
Installation position		Wall
Protection type		IP65
Dimensions		Length 150 mm x Width 133 mm x Height/Depth 75 mm
Diffusor		transparent
Luminous efficacy		103 lm/W
Luminous flux		1000 lm
Rated output P		9.7 W



Colour temperature	5200 K
In-rush current	4.7 A/ 117 μs
Permissible ambient temperature	-25 °C+50 °C
Warranty	3-year

INSTALLATION VIDEO





Discover the full potential of the spotlights.



3D-MODEL: SUN OFL/AFL

Experience this product in the interactive 3D view.

X



CONTACT US
Salutation
Firstname *
Lastname *
Company *
Phone
E-mail-address*
Subject *
Your message *
 Yes, I agree that ESYLUX will inform me about news in the future via newsletter. I have read and agreed to the privacy policy *
* Required

SIMILAR **PRODUCTS**



OTHER PRODUCTS





Solutions

Offices

Education

Health Care Innovations

Demand-driven Automation

Intelligent Lighting

Human Centric Lighting

Light control with DALI-2 Service

Downloads

Knowledge

Support

ESYLUX Services Company

Vision and mission

Experience and quality

Corporate responsibility

Research and development

Cooperations and memberships

∧

References

Highlights

ESYLUX Light Control

DEFENSOR

COMPACT

ESY-Pen

ALVA

FLAT

ISABELLE

Imprint

Privacy policy

Privacy settings

General terms and conditions

Guarantee

Disclaimer

Contact

© 2021 ESYLUX GmbH