SUN OFL/AFL

1 Outdoor lighting | Floodlights | SUN OFL/AFL | 5000 K / 10 W

•

SUN AFL TR 1000 850 MD BK


Item number EL10810084

Offers special product features like

- + Integrated motion detector
- + Overvoltage protection up to 2.5 kV




Device category		Floodlights
Product information	٨	The floodlights are intended for use outdoors. If used inside (e.g. below the ceiling) the heat cannot be sufficiently discharged where necessary.
Installation type		Surface mounting
Installation position		Wall
Protection type		IP65
Dimensions		Length 210 mm x Width 133 mm x Height/Depth 75 mm
Diffusor		transparent
Luminous efficacy		103 lm/W
Luminous flux		1000 lm



Rated output P	9.7 W
Colour temperature	5200 K
Detection angle	160°
Detection range diagonally	12 m
Field of detection	201 m²
In-rush current	2.8 A/ 303 µs
Permissible ambient temperature	-25 °C+40 °C
Warranty	3-year

INSTALLATION VIDEO







Discover the full potential of the spotlights.



3D-MODEL: SUN OFL/AFL

Experience this product in the interactive 3D view.



CONTACT US					
Salutation					
Firstname *					
Lastname *					
Company *					
Phone					
E-mail-address*					
Subject *					
Your message *					
Yes, I agree that ESYLUX will inform me about news in the future via newsletter.					

	I have read and agreed to privacy policy *	o the
* Re	quired	-2

SIMILAR **PRODUCTS**



OTHER PRODUCTS





Solutions
Offices
Education
Health Care Innov ations
Demand-driven Automation
Intelligent Lighting
Human Centric Lighting
Light control with DALI-2 Service
Downloads
Knowledge
Support
ESYLUX Services Company
Vision and mission
Experience and quality

Corporate responsibility

Research and development

Cooperations and memberships

Awards and prizes

References Highlights

ESYLUX Light Control

DEFENSOR

COMPACT

ESY-Pen

ALVA

FLAT

ISABELLE

1

6/6

Image: Image