SUN OFL/AFL

1 Outdoor lighting | Floodlights | SUN OFL/AFL | 3000 K / 30 W

•

SUN OFL TR 3400 830 BK


Item number EL10810114

Offers special product features like

+ Overvoltage protection up to 2.5 kV




Device category	Floodlights
Product information	The floodlights are intended for use outdoors. If used inside (e. g. below the ceiling) the heat cannot be sufficiently discharged where necessary.
Installation type	Surface mounting
Installation position	Wall
Protection type	IP65
Dimensions	Length 267 mm x Width 252 mm x Height/Depth 86 mm
Diffusor	transparent
Luminous efficacy	112 lm/W
Luminous flux	3370 lm
Rated output P	30 W



Colour temperature	3000 K
In-rush current	11.4 A/ 98 µs
Permissible ambient temperature	-25 °C+50 °C
Warranty	3-year

INSTALLATION VIDEO







Discover the full potential of the spotlights.



3D-MODEL: SUN OFL/AFL

Experience this product in the interactive 3D view.



CONTACT US Salutation Firstname * Lastname * Company *

Phone

E-mail-address*

Subject *

Your message *

	Yes, I agree that ESYLUX will inform me about news in the future via newsletter.
	I have read and agreed to the privacy policy *
* R	equired

≣⊠

SIMILAR **PRODUCTS**



OTHER PRODUCTS





Solutions

Offices

Education

Health Care Innovations

Demand-driven Automation

Intelligent Lighting

Human Centric Lighting

Light control with DALI-2 Service

Downloads

Knowledge

Support

ESYLUX Services Company

Vision and mission

Experience and quality

Corporate responsibility

Research and development

Cooperations and memberships

∧

References

Highlights

ESYLUX Light Control

DEFENSOR

COMPACT

ESY-Pen

ALVA

FLAT

ISABELLE

Imprint

Privacy policy

Privacy settings

General terms and conditions

Guarantee

Disclaimer

Contact

© 2021 ESYLUX GmbH