SUN OFL/AFL

1 Outdoor lighting | Floodlights | SUN OFL/AFL | 3000 K / 50 W

•

SUN OFL TR 5400 830 WH

Item number EL10810206

Offers special product features like

+ Overvoltage protection up to 2.5 kV



Device category		Floodlights
Product information		The floodlights are intended for use outdoors. If used inside (e.g. below the ceiling) the heat cannot be sufficiently discharged where necessary.
Installation type	\land	Surface mounting
Installation position		Wall
Protection type		IP65
Dimensions		Length 267 mm x Width 252 mm x Height/Depth 86 mm
Diffusor		transparent
Luminous efficacy		112 lm/W
Luminous flux		5400 lm
Rated output P		48 W



Colour temperature	3100 K
In-rush current	2.6 A/ 322 µs
Permissible ambient temperature	-25 °C+50 °C
Warranty	3-year

ACCESSORIES

MOUNTING



T

FL WALL ARM 700 WH

Item number EL10810527 Wall arm for floodlight, 700 mm, including adapter, white




FL GROUND SPIKE WH

Item number EL10810541 Wall arm for floodlight, including adapter, white



INSTALLATION VIDEO



MORE ON SPOTLIGHTS



Discover the full potential of the spotlights.



3D-MODEL: <mark>SUN</mark> OFL/AFL

Experience this product in the interactive 3D view.



CONTACT US	
Salutation	•
Firstname *	
Lastname *	
Company *	

Phone
E-mail-address*
Subject *
Your message *
Yes, I agree that ESYLUX will inform me about news in the future via newsletter.
I have read and agreed to the privacy policy *
* Required

SIMILAR PRODUCTS



OTHER **PRODUCTS**





Solutions

Offices

~

Health Care Innovations

Demand-driven Automation

Intelligent Lighting

Human Centric Lighting

Light control with DALI-2 Service

Downloads

Knowledge

Support

ESYLUX Services

Company

Vision and mission

Experience and quality

Corporate responsibility

Research and development

Cooperations and memberships

Awards and prizes

References

Highlights

ESYLUX Light Control

DEFENSOR

COMPACT

ESY-Pen

ALVA

FLAT

ISABELLE

Imprint			
Privacy policy			
Privacy settings			
General terms and conditions			
Guarantee			
Disclaimer			
Contact			
		6/7	

