



♠ | Outdoor lighting | Floodlights | SUN OFL/AFL | 3000 K / 50 W



SUN OFL TR 5400 830 BK

Item number EL10810213

Offers special product features like


+ Overvoltage protection up to 2.5 kV



TECHNICAL DATA

DOWNLOADS


LIGHT CALCULATION



Device category	Floodlights
Product information	The floodlights are intended for use outdoors. If used inside (e. g. below the ceiling) the heat cannot be sufficiently discharged where necessary.
Installation type	Surface mounting
Installation position	Wall
Protection type	IP65
Dimensions	Length 267 mm x Width 252 mm x Height/Depth 86 mm
Diffusor	transparent
Luminous efficacy	112 lm/W
Luminous flux	5400 lm
Rated output P	48 W

Colour temperature	3100 K
In-rush current	2.6 A/ 322 µs
Permissible ambient temperature	-25 °C+50 °C
Warranty	3-year

INSTALLATION VIDEO







Discover the full potential of the spotlights





3D-MODEL: SUN OFL/AFL

Experience this product in the interactive 3D view.





CONTACT US
Salutation
Firstname *
Lastname *
Company *
Phone
E-mail-address*
Subject *
Your message *
Yes, I agree that ESYLUX will inform me about news in the future via newsletter.
I have read and agreed to the privacy policy *
* Required

SIMILAR PRODUCTS



OTHER PRODUCTS







Solutions

Offices

Education

Health Care Innovations

IIIIOV audio

Demand-driven Automation

Intelligent Lighting

Human Centric Lighting

Light control with DALI-2

Service

Downloads

Knowledge

Support

ESYLUX Services

Company

Vision and mission

Experience and quality

Corporate responsibility

Research and development

Cooperations and memberships

Awards and prizes

References Highlights **ESYLUX Light Control DEFENSOR** COMPACT ESY-Pen ALVA FLAT ISABELLE Imprint Privacy policy Privacy settings General terms and conditions | Guarantee Disclaimer Contact © 2021 ESYLUX GmbH