



•



SUN AFL TR 5400 830 MD WH

Item number EL10810220

Offers special product features like

- + Integrated motion detector
- + Overvoltage protection up to 2.5 kV





Device category		Floodlights
Product information	٨	The floodlights are intended for use outdoors. If used inside (e. g. below the ceiling) the heat cannot be sufficiently discharged where necessary.
Installation type		Surface mounting
Installation position		Wall
Protection type	VIII	IP65
Dimensions	V	Length 290 mm x Width 250 mm x Height/Depth 86 mm
Diffusor	•	transparent
Luminous efficacy		112 lm/W
Luminous flux		5400 lm

Rated output P	48 W
Colour temperature	3100 K
Detection angle	160°
Detection range diagonally	12 m
Field of detection	201 m²
In-rush current	2.6 A/ 322 µs
Permissible ambient temperature	-25 °C+40 °C
Warranty	3-year

ACCESSORIES

MOUNTING



FL WALL ARM 700 WH

Item number EL10810527
Wall arm for floodlight, 700 mm, including adapter, white







FL GROUND SPIKE WH

Item number EL10810541
Wall arm for floodlight, including adapter, white





INSTALLATION VIDEO







SIMILAR PRODUCTS





OTHER PRODUCTS







Solutions

Offices

Education

Health Care Innovations

Demand-driven Automation

Intelligent Lighting

Human Centric Lighting

Light control with DALI-2

Service

Downloads

Knowledge

Support

ESYLUX Services

Company

Vision and mission

Experience and quality

Corporate responsibility

Research and development

Cooperations and memberships

Awards and prizes

References Highlights **ESYLUX Light Control DEFENSOR** COMPACT ESY-Pen ALVA FLAT **ISABELLE** Imprint Privacy policy Privacy settings General terms and conditions | Guarantee Disclaimer Contact © 2021 ESYLUX GmbH