BOLLARD LIGHTS

AIVA



Culdus lighting | Bullard lights | ALVA | 3000 K/300 / 940 HHH/20 HOTHIN



72h

ALVA BL 940/170 OP 360° 800 830 DALI AN

Item number EL10820243

Offers special product features like

+ Protected against sea air



Device category	Bollard light
Installation type	Free standing
Installation position	Floor
Protection type	IP65
Dimensions	Height/Depth 940 mm, Ø 170 mm
Diffusor	opal
Luminous efficacy	60 lm/W
Luminous flux	1030 lm
Rated output P	17 W
Colour temperature	3100 K
In-rush current	12 A/ 57 μs
Permissible ambient temperature	-25 °C+40 °C
Warranty	5 years

ACCESSORIES

MOUNTING



ALVA GROUND ANCHOR


 $Item \ number \ EL10820083$

Ground anchor galvanised for installation of bollard lights in concrete foundation or solid ground





INSTALLATION VIDEO





Discover the full potential of the ALVA series.





CATALOGUE 2020/2021



CONTACT US	
Salutation	
Firstname *	
Lastname *	
Company *	
Phone	
E-mail-address*	
Subject *	
Your message *	
Yes, I agree that ESYLUX will inform me about news in the future via newsletter. I have read and agreed to the privacy policy *	
* Required	

OTHER PRODUCTS





Solutions

Offices

Education

Health Care **Innovations** Demand-driven Automation Intelligent Lighting Human Centric Lighting Light control with DALI-2 Service Downloads Knowledge Support **ESYLUX Services** Company Vision and mission Experience and quality Corporate responsibility Research and development Cooperations and memberships Awards and prizes References Highlights **ESYLUX Light Control DEFENSOR** COMPACT ESY-Pen ALVA FLAT **ISABELLE Imprint** Privacy policy Privacy settings General terms and conditions | Guarantee

Disclaimer Contact

© 2021 ESYLUX GmbH