

💼 | Indoor lighting | Emergencylights | ELH



ELH EL LED 3h SC SM CORRIDOR

Item number EN10080005

The ELH series provides escape route lighting for single-battery operation with a lens construction that is specially designed for extensive areas — either for oval illumination of floors or circular illumination of large rooms. Its larger-than-average range reduces the number of lights required. The integrated DALI interface ensures high levels of control flexibility during operation and convenient maintenance.



Device category	Safetylight
Installation type	Surface mounting
Installation position	Ceiling
Protection type	IP20
Dimensions	Length 190 mm x Width 190 mm x Height/Depth 44 mm
Luminous efficacy	38 lm/W
Luminous flux	155 lm
Rated output P	4 W
Colour temperature	approx 4500 K
In-rush current	1.3 A/457 μs



Permissible ambient temperature	5 °C+35 °C
Warranty	5 years

ACCESSORIES

BATTERY

Internal Arabi

ELH SM BATTERY NiCd 2000mAh

Item number EN00007378 Battery for ELH series, 2000 mAh, surface-mounted version





CONTACT US	
Salutation	•
Firstname *	
Lastname *	
Company *	
Phone	
E-mail-address*	
Subject *	

Yo	our message *
	Yes, I agree that ESYLUX will inform me about news in the future via newsletter.
	I have read and agreed to the privacy policy *
* Re	quired
	≡⊠

SIMILAR **PRODUCTS**

OTHER PRODUCTS





Solutions

Offices

Education

Health Care Innovations

Demand-driven Automation

Intelligent Lighting

Human Centric Lighting

Light control with DALI-2 Service

Downloads

Knowledge

Support

. . .

ESYLUX Services Company

Vision and mission

Experience and quality

Corporate responsibility

Research and development

Cooperations and memberships

Awards and prizes

References

Highlights

ESYLUX Light Control

DEFENSOR

COMPACT

ESY-Pen

ALVA

FLAT

ISABELLE

