


EPIC® H-B 24 AG-LB

Housing design H-B. The industry standard.

The universal metal housing with a single lever and a seal is able to withstand temperatures of approximately +125 degrees for a short period.

Info

Universal, robust metal housings size H-B 24 Single Lever version for quick locking and simple unlocking with lifting aid Protection rating UL50E tested







Supplementary automation components from Lapp



Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

Benefits Safe fixing with 4 screws

Application range

Plant engineering Light & sound technology Plastics industry

Last Update (09.10.2020) ©2020 Lapp Group - Technical changes reserved Product Management www.lappkabel.de You can find the current technical data in the corresponding data sheet. PN 0456 / 02_03.16



EPIC® H-B 24 AG-LB

Product features

H-A case: Wall base Single lever Included: flat gasket

Technical Data	
Classification ETIM 5:	ETIM 5.0 Class-ID: EC000437 ETIM 5.0 Class-Description: Housing for industrial connectors
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000437 ETIM 6.0 Class-Description: Housing for industrial connectors
Material:	Housing: powder-coated aluminium alloy, grey Lever: zinc-plated steel Sealing: NBR
Protection rating:	IP 65 (latched) NEMA 250, UL50E: 12 (latched)
VDE-tested:	Certified production control: VDE-REG. no.: B437 UL-tested: UL File Number: E75770
Temperature range:	-40°C to +100°C, short-term up to +125°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Article description	M	Pieces / PU	
H-B housing: panel-mount bas	e (single lever)			
10102900	H-B 24 AG-LB	AG	5	
Article number H-B housing: panel-mount bas 10102900				

EPIC® H-B 24 AG-LB