


## Product Description

High mechanic stability; Lateral sealing lips fit automatically around various cable dimensions; Optimal strain relief; Large clear opening allows clamping of up to two flat cables



## Application range

- For inserting of flat cables.
- Conveyor systems
- Pumps
- Elevators
- Switch cabinet building

## Benefits

- High mechanic stability
- Lateral sealing lips fit automatically around various cable dimensions
- Optimal strain relief
- Large clear opening allows clamping of up to two flat cables

## Design

- PG connection thread

## Note

- For suitable flat cables, see ÖLFLEX® LIFT F for indoor applications or ÖLFLEX® CRANE F for outdoor applications
- Counter nut to be used SKINDICHT® SM



Technical Data

**Caution**

Installation dimensions see Appendix T21

**On request**

Available with long connection thread

**Material**

Body: Nickel plated brass Special sealing insert:

CR

**Degree of protection**

IP 54

**Range of temperature**

-20°C up to +100°C

Article List

Part number	Part designation / size	Flat cable width min./ max.	Min./ max. cable thickness in mm	SW1 / SW2 mm	Overall length C mm	Thread length D mm	Pieces / PU
SKINDICHT® SVF							
52005480	PG 16	-- 16	-- 5	24 / 22	27,5	6.5	25
52005490	PG 21	9 - 21	3 - 8	30 / 28	30	7	25
52005500	PG 29	14 - 30	4 - 11,5	40 / 37	31,5	8	10
52005510	PG36	24 - 40	4 - 11,5	50 / 47	36	9	10
52005520	PG 42	29 - 45	5 - 12	57 / 54	40	10	5
52005530	PG 48	34 - 50	5 - 12	64 / 60	41,5	10	5

**Footnote:**

Photographs are not to scale and do not represent detailed images of the respective products.