


Product Description

Maximum reliability; Optimal strain relief; Large, variable clamping ranges



Application range

- In areas with high demands on special mechanical and chemical stability.
- Chemical industry
- Measurement and control technology
- Machine and apparatus construction
- Plant engineering

Benefits

- Maximum reliability
- Optimal strain relief
- Large, variable clamping ranges

Design

- PG connection thread

Note

- Counter nut to be used SKINDICHT® SM
- For suitable accessories see SKINTOP® accessories PG



Technical Data

Caution

Installation dimensions and tightening torques see Appendix T21

Material

Body: Nickel plated brass Insert: Polyamide Seal: CR O-ring: NBR

Degree of protection

IP 68 - 5 bar

Range of temperature

-30°C up to +100°C

Article List

| Part number | Part designation / size | Clamping range ØF mm | SW mm | Overall length C mm | Thread length D mm | Pieces / PU |
|-------------|-------------------------|----------------------|-------|---------------------|--------------------|-------------|
| SKINTOP® MS | | | | | | |
| 52015700 | MS 7 | 2 - 6,5 | 14 | 25 | 5 | 100 |
| 52015710 | MS 9 | 4 - 8 | 17 | 29 | 6 | 100 |
| 52015720 | MS 11 | 4 - 10 | 20 | 32 | 6 | 50 |
| 52015730 | MS 13,5 | 5 - 12 | 22 | 34 | 6.5 | 50 |
| 52015740 | MS 16 | 8 - 14 | 24 | 35 | 6.5 | 50 |
| 52015750 | MS 21 | 11 - 18 | 30 | 40 | 7 | 25 |
| 52015760 | MS 29 | 16 - 25 | 40 | 48 | 8 | 25 |
| 52015765 | MS 36 | 19 - 32 | 50 | 62 | 15 | 10 |
| 52015766 | MS 42 | 28 - 38 | 57 | 62 | 15 | 5 |
| 52015767 | MS 48 | 34 - 44 | 64 | 62 | 15 | 5 |

Footnote:

Photographs are not to scale and do not represent detailed images of the respective products.