


SKINTOP® halogen-free

### Product Description

Maximum reliability;Extremely flame retardant according to UL 94 V0;Completely halogen-free (inclusive seal material);Self extinguishing, no dripping;Permanent vibration protection



### Application range

- Where personal and property protection is a priority.
- Public buildings
- Ventilation systems
- Tunnel construction
- Underground railways and trains

### Benefits

- Maximum reliability
- Extremely flame retardant according to UL 94 V0
- Completely halogen-free (inclusive seal material)
- Self extinguishing, no dripping
- Permanent vibration protection

### Design

- Metric connection thread acc. to EN 50262



**Technical Data**

**Caution**

Installation dimensions and tightening torques see Appendix T21

**Colour delivered**

RAL 7035 light grey

**Material**

Polyamide UL94 V0 - halogen-free Seal: LSE 1 - halogen-free O-ring: LSE 1 - halogen-free

**Tests**

Filament wire test EN 60695-2-1/1 +960°C

**Degree of protection**

IP 68 - 5 bar

**Range of temperature**

-20°C up to +100°C

**Article List**

Part number	Part designation / size	Clamping range ØF mm	SW mm	Overall length C mm	Thread length D mm	Pieces / PU
SKINTOP® ST-HF-M						
53111407	ST-HF-M 12 x 1,5	4-5,5	15	30	8	100
53111417	ST-HF-M 16 x 1,5	4,5-9	19	34	8	100
53111427	ST-HF-M 20 x 1,5	7-13	25	37	9	100
53111437	ST-HF-M 25 x 1,5	9-17	30	40	10	50
53111447	ST-HF-M 32 x 1,5	11-21	36	47	10	25
53111457	ST-HF-M 40 x 1,5	19-28	46	52	10	10
53111467	ST-HF-M 50 x 1,5	27-35	55	62	12	5
53111477	ST-HF-M 63 x 1,5	34-45	66	71	12	5

**Footnote:**

Photographs are not to scale and do not represent detailed images of the respective products.