


Product Description

Benefits see SKINTOP® MS-M



Application range

- With reducing seal insert, to seal cables with smaller outer diameters.

Benefits

- Benefits see SKINTOP® MS-M

Design

- Metric connection thread acc. to EN 50262

Note

- Counter nut to be used SKINDICHT® SM-M
- For suitable accessories see SKINTOP® metric accessories



Technical Data

Caution

Installation dimensions and tightening torques see Appendix T21

Approvals

IP 69 K approval for sizes M75x1,5 to M110x2 pending UL, CSA, DNV, VDE approval for size M90x2 to M110x2 pending

Material

Body: Nickel plated brass Insert: Polyamide Seal: CR O-ring: NBR

Degree of protection

IP 68
IP 69 K

Range of temperature

-30°C up to +100°C

Article List

Part number	Part designation / size	Clamping range ØF mm	SW mm	Overall length C mm	Thread length D mm	Pieces / PU
SKINTOP® MSR-M						
53112100	12 x 1,5	1-5	16	26,5	6.5	100
53112110	16 x 1,5	2-7	20	32	7	100
53112120	20 x 1,5	5-10	24	35,5	8	50
53112130	25 x 1,5	6-13	29	37,5	8	25
53112140	32 x 1,5	7-15	36	42,2	9	25
53112150	40 x 1,5	15-23	45	49,5	9	10
53112160	50 x 1,5	22-29	54	52	10	5
53112170	63 x 1,5	28-39	67	61,3	15	5
53112511	75 x 1,5	53-63	95	105	15	1
53112515	110 x 2	76-88	135	154	25	1

Footnote:

Photographs are not to scale and do not represent detailed images of the respective products.