

Product Description

Benefits see SKINTOP® CLICK



Application range

- With reducing seal insert, to seal cables with smaller outer diameters.

Benefits

- Benefits see SKINTOP® CLICK

Approvals (Norm references)

- UL File Nr. E79903

Scope of delivery

- Disassembly tool contained in the delivery scope

**Technical Data****Colour delivered**

RAL 7001 silver-grey RAL 7035 light grey RAL
9005 black / UV resistant

Range of temperature

Static: -40°C up to +100°C
Dynamic: -20°C up to +100°C

Material

Body: special polyamide Seal: special elastomer

Article List

Part number	Part designation / size	Clamping range ØF mm	M (hole mm)	SW1 / SW2 mm	Overall length C mm	Thread length D mm	S (wall thickness mm)	Pieces / PU
SKINTOP® CLICK-R light grey								
53112925	CLICK-R 12	1 - 5	12,3 (-0,2)	15 / 18	40	8	1 - 4	50
53112689	CLICK-R 16	4 - 7	16,3 (-0,2)	19 / 22	42	8	1 - 4	50
53112690	CLICK-R 20	5 - 10	20,3 (-0,2)	25 / 27	45,5	8	1 - 4	25
53112691	CLICK-R 25	6 - 13	25,3 (-0,2)	30 / 34	48,5	8	1 - 4	25
53112926	CLICK-R 32	7 - 15	32,3 (-0,2)	36 / 40	55	8	1 - 4	25
SKINTOP® CLICK-R silver grey								
53112927	CLICK-R 12	1 - 5	12,3 (-0,2)	15 / 18	40	8	1 - 4	50
53112879	CLICK-R 16	4 - 7	16,3 (-0,2)	19 / 22	42	8	1 - 4	50
53112880	CLICK-R 20	5 - 10	20,3 (-0,2)	25 / 27	45,5	8	1 - 4	25
53112881	CLICK-R 25	6 - 13	25,3 (-0,2)	30 / 34	48,5	8	1 - 4	25
53112928	CLICK-R 32	7 - 15	32,3 (-0,2)	36 / 40	55	8	1 - 4	25
SKINTOP® CLICK-R black								



53112929	CLICK-R 12	1 - 5	12,3 (-0,2)	15 / 18	40	8	1 - 4	50
53112885	CLICK-R 16	4 - 7	16,3 (-0,2)	19 / 22	42	8	1 - 4	50
53112886	CLICK-R 20	5 - 10	20,3 (-0,2)	25 / 27	45,5	8	1 - 4	25
53112887	CLICK-R 25	6 - 13	25,3 (-0,2)	30 / 34	48,5	8	1 - 4	25
53112931	CLICK-R 32	7 - 15	32,3 (-0,2)	36 / 40	55	8	1 - 4	25

Footnote:

Photographs are not to scale and do not represent detailed images of the respective products.