

Product Description

Optimum seal when using AS-I bus cables; Easy insertion of pre assembled cables (with fieldbus or RJ-45 connector); Strain relief



Application range

- This seals can be used instead of our standard seals in the SKINTOP® cable glands.
- Switch cabinets
- Control panels
- Office applications
- Automation technology

Benefits

- Optimum seal when using AS-I bus cables
- Easy insertion of pre assembled cables (with fieldbus or RJ-45 connector)
- Strain relief

Design

- True to dimension cut for AS-I bus cables
- Seal with hole and cut for easy insertion of pre assembled RJ-45 network cables
- Seal with hole and cut for easy insertion of pre assembled fieldbus cables
- Multiple seal inserts with holes and cuts for easy insertion of pre assembled cables

Note

- IP 68 can be achieved if the hole is optimally occupied, i. e. when using standard AS-I bus cables



Technical Data

Colour delivered

RAL 9005 black

Material

NBR

Degree of protection

IP 54

Range of temperature

-40°C up to +100°C

Article List

Part number	Part designation / size	Number of cables x Cable Ø	Pieces / PU
SKINTOP® DIX-M ASI			
53611001	M 20	1 x AS-I	50
SKINTOP® DIX-M ASI DUO			
53611004	M 25	2 x AS-I	50
SKINTOP® DIX-M RJ-45			
53440980	M 25	1 x 5,4	50
SKINTOP® DIX-M FIELDBUS			
53440970	M 32	1 x 6,5	50
SKINTOP® DIX-M CUTTED			
53310444	M 40	3 x 10	25

Footnote:

Photographs are not to scale and do not represent detailed images of the respective products.