




## ÖLFLEX® HEAT 180 EWKF

Silicone cables with increased mechanical characteristics



**Info**

- Proven notch-resistant EWKF quality

### Benefits

- Longer durability in harsh applications than conventional silicone cables
- Notch and tear-resistant silicone compounds reduce damage due to mechanical stress
- Due to the use of special additives in EWKF silicone, armoured cable versions will not be required
- Flexibility simplifies installation where space is limited
- Possesses insulating properties after combustion due to remaining SiO<sub>2</sub> ash on the conductor

### Application range

- Areas with high ambient temperatures and occasionally mechanical stress
- Typical fields of application
  - Steel, ceramic and iron works
  - Bakery equipment and industrial furnaces
  - Electric motor industry
  - Sauna/solarium construction
  - Thermal and heating elements
  - Lighting technology
  - Ventilator engineering
  - Air-conditioning technology
  - Galvanisation technology

### Product features

- EWKF:**
  - Initial tear propagation and notch resistance
- Halogen-free (IEC 60754-1), no corrosive gases (IEC 60754-2), flame-retardant (IEC 60332-1-2)
- Good hydrolysis and UV-resistance
- Resistant to a multitude of oils, alcohols, vegetable and animal fats and chemical substances
- Adequate ventilation must be ensured, since the mechanical properties of silicone cables decrease from +100°C in the absence of air

### Norm references / Approvals

- Based on EN 50525-2-83

### Product Make-up

- Fine-wire, tinned-copper conductor
- Core insulation: based on EWKF silicone
- Cores twisted together
- Outer sheath: silicone-based EWKF, notch-resistant, black

### Technical data

**Classification**  
ETIM 5.0 Class-ID: EC001578  
ETIM 5.0 Class-Description: Flexible cable

**Core identification code**  
Colours according to VDE 0293-308, refer to Appendix T9  
From 6 cores: black with white numbers

**Conductor stranding**  
Fine wire according to VDE 0295 Class 5 / IEC 60228 Class 5

**Minimum bending radius**  
Occasional flexing: 15 x outer diameter  
Fixed installation: 4 x outer diameter

**Nominal voltage**  
U<sub>0</sub>/U: 300/500 V

**Test voltage**  
2000 V

**Protective conductor**  
G = with GN-YE protective conductor  
X = without protective conductor

**Temperature range**  
-50 °C to +180 °C  
(adequate ventilation required)

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
<b>ÖLFLEX® HEAT 180 EWKF</b>				
0046500	2 X 0.75	6.4	15	49
0046501	3 G 0.75	6.9	22	60
00465023	4 G 0.75	7.6	29	76
00465033	5 G 0.75	8.5	36	96
0046506	2 X 1	6.8	20	56
0046507	3 G 1	7.1	29	68
00465083	4 G 1	7.9	39	88
00465093	5 G 1	8.8	48	110
0046110	7 G 1	9.5	67.2	137
0046511	2 X 1.5	8.0	29	77
0046512	3 G 1.5	8.4	43	94
00465133	4 G 1.5	9.5	58	117
00465143	5 G 1.5	10.4	72	143

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0046115	7 G 1.5	11.0	101	180
0046116	12 G 1.5	14.9	173	319
0046117	16 G 1.5	17.1	230.4	424
0046119	24 G 1.5	21.0	345.6	637
0046520	2 X 2.5	9.4	48	110
0046521	3 G 2.5	9.8	72	146
00465223	4 G 2.5	11.1	96	181
00465233	5 G 2.5	12.4	120	222
0046131	3 G 4	11.5	114	213
00461323	4 G 4	12.5	152	267
00461333	5 G 4	13.9	190	334
0046141	3 G 6	13.2	174	297
00461423	4 G 6	14.7	232	381
00461433	5 G 6	16.5	290	481

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)  
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum  
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).  
Photographs are not to scale and do not represent detailed images of the respective products.

### Similar products

- ÖLFLEX® HEAT 180 H05SS-F EWKF refer to page 177
- ÖLFLEX® HEAT 180 EWKF C refer to page 181

### Accessories

- SILVYN® AS refer to page 896
- SKINDICHT® SHV-M refer to page 756
- SILVYN® EDU-AS refer to page 898
- KS 20 cable shears refer to page 999