



ÖLFLEX® FD 855 P

TPE-insulated, numbered, PUR sheath



Info

- Extended Line for heavy duty in power chain applications
- Smallest bending radii of all FD cables

Benefits

- Well-proven and reliable
- Various applications
- Suitable for all weather conditions

Application range

- In power chains or moving machine parts
- Particularly in wet areas of machine tools and transfer lines
- Mechanical engineering
- Construction machinery
- Assembly lines, production lines, in all kinds of machines

Product features

- Low-adhesive surface
- Oil-resistant
- Halogen-free and flame-retardant (IEC 60332-1-2)
- In dry, damp or wet interiors with normal mechanical stress conditions
- Designed for 5 up to 10 million bending/unbending cycles in the power chain.

Norm references / Approvals

- Based on VDE 0250 / 0285
- For travel distances up to 100 m (horizontal)
- For use in power chains: Please comply with the assembly guidelines listed in Appendix T3

Product make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: TPE
- Cores twisted together in extremely short lay lengths
- Non-woven wrapping
- PUR outer sheath, grey (RAL 7001)

Technical data

Classification
ETIM 5.0 Class-ID: EC000104
ETIM 5.0 Class-Description: Control cable

Core identification code
Black with white numbers acc. to VDE 0293-1

Specific insulation resistance
> 20 GOhm x cm

Conductor stranding
Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6

Minimum bending radius
For flexible use: 5 x outer diameter
Fixed installation: 3 x outer diameter

Nominal voltage
IEC U₀/U: 300/500 V

Test voltage
3000 V

Protective conductor
G = with GN-YE protective conductor
X = without protective conductor

Temperature range
Flexing: -40°C to +80°C
Fixed installation: -50°C to +90°C

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0027530	2 X 0.5	5.1	10.0	34
0027531	3 G 0.5	5.5	14.0	40
0027532	5 G 0.5	6.6	24.0	55
0027533	6 G 0.5	7.1	29.0	63
0027534	7 G 0.5	7.7	34.0	76
0027535	12 G 0.5	9.1	58.0	114
0027536	18 G 0.5	10.9	86.0	165
0027537	20 G 0.5	11.5	96.0	180
0027538	25 G 0.5	13.4	120.0	219
0027540	30 G 0.5	13.6	144.0	251
0027541	36 G 0.5	14.7	173.0	290
0027545	2 X 0.75	5.6	14.0	42
0027546	3 G 0.75	6.0	22.0	50
0027547	4 G 0.75	6.7	29.0	60
0027548	5 G 0.75	7.3	36.0	71
0027549	7 G 0.75	8.8	50.0	99
0027550	12 G 0.75	10.3	86.0	158
0027551	18 G 0.75	12.4	130.0	219
0027552	20 G 0.75	13.3	144.0	240
0027553	25 G 0.75	15.5	180.0	309
0027555	36 G 0.75	16.9	259.0	411
0027560	2 X 1.0	6.0	19.0	50
0027561	3 G 1.0	6.5	29.0	61
0027562	4 G 1.0	7.2	38.0	70
0027563	5 G 1.0	7.8	48.0	93

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0027564	7 G 1.0	9.5	67.0	122
0027565	12 G 1.0	11.2	115.0	196
0027566	18 G 1.0	13.7	173.0	274
0027567	20 G 1.0	14.4	192.0	300
0027568	25 G 1.0	16.8	240.0	385
0027570	30 G 1.0	17.0	288.0	444
0027571	36 G 1.0	18.6	346.0	516
0027575	2 X 1.5	6.7	29.0	68
0027576	3 G 1.5	7.3	43.0	83
0027586	4 G 1.5	8.0	58.0	100
0027577	5 G 1.5	9.0	72.0	128
0027578	7 G 1.5	10.7	101.0	177
0027579	12 G 1.5	12.7	173.0	275
0027580	18 G 1.5	15.2	259.0	405
0027582	25 G 1.5	18.8	360.0	565
0027584	30 G 1.5	18.8	432.0	652
0027585	36 G 1.5	20.6	518.0	759
0027587	41 G 1.5	22.4	614.0	978
0027370	3 G 2.5	8.9	72.0	121
0027371	4 G 2.5	9.9	96.0	163
0027372	5 G 2.5	11.0	120.0	196
0027373	7 G 2.5	13.4	168.0	266
0027374	12 G 2.5	15.8	288.0	446
0027375	18 G 2.5	18.9	432.0	665
0027376	25 G 2.5	23.5	600.0	929

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® CHAIN 896 P refer to page 126

Accessories

- SILVYN® CHAIN cable protection and guiding systems

ÖLFLEX®
 UNITRONIC®
 ETHERLINE®
 HITRONIC®
 EPIC®
 SKINTOP®
 SILVYN®
 FLEXIMARK®
 ACCESSORIES
 APPENDIX