



## UNITRONIC® LiHCH

Screened halogen-free data transmission cable with colour code acc. to DIN 47100

LAPP KABEL STUÏGART UNITRONIC® LiHCH



Info

- For use within public buildings and industrial plants

### Benefits

- Halogen-free: to protect human life and valuable assets in the event of a fire, through low smoke density and low amount of corrosive gases
- Low capacitance due to polyolefin-based insulation
- Overall braid minimises electrical interference

### Application range

- Suitable for areas with a high density of people as well as high-value property that must be protected in the event of a fire
- For use within public buildings, transport systems and industrial plants
- For data processing, measurement and control engineering, safety related systems and as electronics cable
- For use in computer systems, instrumentation systems, office equipment, balances - wherever screened, halogen-free, small-diameter cables are needed.
- 7-wire stranded conductor can be used for Maxi TERMI-POINT® wiring (for this product the 0,34mm<sup>2</sup> version only)

### Product features

- Flame-retardant according IEC 60332-1-2
- Low smoke zero halogen (LSZH)
- Halogen-free according to IEC 60754-1 (amount of halogen acid gas)  
Corrosiveness of combustion gases according to EN 50267-2-3 (degree of acidity)
- Low smoke density according to IEC 61034-2

### Norm references / Approvals

- Based on VDE 0812

### Product make-up

- Fine-wire/multi-wire (0.34 mm<sup>2</sup>) strand made of bare copper wires
- Core insulation made of special halogen-free compound
- Tinned-copper braiding
- Outer sheath made of special halogen-free compound  
Outer sheath colour: pebble grey (RAL 7032)

### Technical data

- Core identification code**  
DIN 47100 without colour repetition, refer to Appendix T9
- Mutual capacitance**  
C/C approx. 80 nF/km  
C/S approx. 120 nF/km
- Peak operating voltage**  
(not for power applications) 250 V
- Specific insulation resistance**  
> 20 GOhm x cm
- Inductivity**  
approx. 0.65 mH/km
- Conductor stranding**  
Stranded, fine-wire  
0.34 mm<sup>2</sup>: 7-wire
- Minimum bending radius**  
Occasional flexing: 10 x outer diameter  
Fixed installation: 6 x outer diameter
- Test voltage**  
1200 V
- Temperature range**  
Occasional flexing: -5°C to +70°C  
Fixed installation: -30°C to +80°C

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
<b>UNITRONIC® LiHCH</b>				
0037302	2 x 0.14	4.1	12.0	22
0037303	3 x 0.14	4.3	14.1	25
0037304	4 x 0.14	4.5	15.9	29
0037306	6 x 0.14	5.1	22.0	35
0037307	7 x 0.14	5.1	24.0	38
0037308	8 x 0.14	6.0	26.0	41
0037312	12 x 0.14	6.5	30.4	78
0037316	16 x 0.14	7.2	43.0	90
0037325	25 x 0.14	8.7	63.0	149
0037402	2 x 0.25	4.7	15.0	25
0037403	3 x 0.25	4.9	18.0	30
0037404	4 x 0.25	5.2	22.0	35
0037406	6 x 0.25	6.2	30.0	49
0037407	7 x 0.25	6.2	32.0	52
0037408	8 x 0.25	7.3	35.0	58
0037410	10 x 0.25	7.7	42.0	81
0037425	25 x 0.25	10.9	114.0	172
0037502	2 x 0.34	5.1	17.0	30
0037503	3 x 0.34	5.3	21.0	35
0037504	4 x 0.34	5.9	25.0	42
0037505	5 x 0.34	6.4	30.0	53
0037507	7 x 0.34	7.0	42.0	73
0037508	8 x 0.34	8.0	45.0	84
0037510	10 x 0.34	8.5	63.0	101

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0037516	16 x 0.34	9.6	94.0	160
0037525	25 x 0.34	12.1	144.0	259
0037602	2 x 0.5	5.8	29.0	38
0037603	3 x 0.5	6.1	35.0	47
0037604	4 x 0.5	6.5	45.0	67
0037605	5 x 0.5	7.2	50.0	76
0037606	6 x 0.5	7.8	59.0	84
0037607	7 x 0.5	7.8	68.0	91
0037608	8 x 0.5	8.9	75.0	135
0037610	10 x 0.5	9.5	93.0	131
0037612	12 x 0.5	9.8	99.0	177
0037618	18 x 0.5	11.7	134.0	239
0037625	25 x 0.5	13.9	211.0	352
0037702	2 x 0.75	6.2	35.0	45
0037703	3 x 0.75	6.5	46.0	69
0037704	4 x 0.75	7.2	56.0	80
0037705	5 x 0.75	7.8	70.0	99
0037707	7 x 0.75	8.3	90.0	120
0037802	2 x 1	6.5	43.0	72
0037803	3 x 1	7.0	56.0	90
0037804	4 x 1	7.5	68.0	109
0037807	7 x 1	8.8	118.0	171
0037902	2 x 1.5	7.7	58.0	90
0037903	3 x 1.5	8.1	74.0	115
0037905	5 x 1.5	9.5	129.0	176

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

TERMI-POINT® is a registered trademark of AMP

Photographs are not to scale and do not represent detailed images of the respective products.

### Similar products

- UNITRONIC® LiHCH (TP) refer to page 265

### Accessories

- SKINTOP® MS-SC-M refer to page 674
- Multipurpose shears A and B refer to page 907