

EPIC® H-A 3 TS

Innovative metal and plastic housing design

The robust compact plastic housing has a side cable entry and is suitable for use in machine and device manufacturing.

Info

Lightweight, chemically resistant plastic housing Protection rating UL50E tested













Waterproof



Robust



Mechanical resistance



Mechanical and plant engineering

Benefits

Housing in plastic or metal version. For power supply in the smallest possible space

Application range

Machine and equipment manufacturing Control engineering Electronic laboratory

Product features

Hood Bolts for single lever Side cable entry Versions with / without cable gland

Last Update (08.10.2021)
©2021 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16





EPIC® H-A 3 TS

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: thermoplastic, grey, black

Lever: zinc-plated steel

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range: -40°C to +100°C, short-term up to +125°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

& LAPP

EPIC® H-A 3 TS

Article number	Article description	М	PG	Material	Colour	Cable gland	Cable clamping range
10427300	H-A 3 Ts	-	11	Thermoplastic	black	-	-
10427000	H-A 3 Ts	-	11	Thermoplastic	grey	-	-
10620600	H-A 3 Ts	-	11	Thermoplastic	black	yes	6.5 - 12
10427100	H-A 3 Ts	-	11	Thermoplastic	grey	yes	6.5 - 12
19427300	H-A 3 Ts M20	20	-	Thermoplastic	black	-	-
19427000	H-A 3 Ts M20	20	-	Thermoplastic	grey	-	-



EPIC® H-A 3 TS

