

## EPIC® H-A 3 AG

Innovative metal and plastic housing design

The compact plastic or metal housing for rectangular connectors is ideal for use in restricted spaces.

### Info

Lightweight, chemically resistant plastic housing

Protection rating UL50E tested



Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

### Benefits

Housing in plastic or metal version for safe connections in the smallest possible space

### Application range

Machine and equipment manufacturing

Control engineering

Electronic laboratory

### Product features

H-A case: Wall base

1 lever

Anbauehäuse mit Deckel (mit Dichtung, für Buchseneinsätze)

Panel-mount base, flat gasket included (version with open base)

Last Update (27.10.2021)

©2021 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## EPIC® H-A 3 AG

Included: flat gasket

### Technical Data

|                        |   |
|------------------------|---|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC000437<br>ETIM 5.0 Class-Description: Housing for industrial connectors  |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC000437<br>ETIM 6.0 Class-Description: Housing for industrial connectors  |
| Material:              | Housing: powder-coated zinc die-casting, grey<br>Lever: zinc-plated steel<br>Sealing: NBR<br>Housing: grey thermoplastic, black<br>Lever: zinc-plated steel<br>Sealing: NBR |
| Protection rating:     | IP 65 (latched)<br>NEMA 250, UL50E: 12, 4 (latched)   |
| VDE-tested:            | Certified production control: VDE-REG. no.: B437<br>UL-tested:<br>UL File Number: E75770  |
| Temperature range:     | -40°C to +100°C, short-term up to +125°C  |

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

**EPIC® H-A 3 AG**

| Article number                           | Article description | M  | Material         | Colour | Pieces / PU |
|--|---------------------|----|------------------|--------|-------------|
| H-A housing: panel-mount base (straight) |                     |    |                  |        |             |
| 10422500                                 | H-A 3 Mag           | AG | Zinc die-casting | grey   | 10          |
| 10422200                                 | H-A 3 Ag            | AG | Thermoplastic    | black  | 10          |
| 10422000                                 | H-A 3 Ag            | AG | Thermoplastic    | grey   | 10          |

Last Update (27.10.2021)

©2021 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

**EPIC® H-A 3 AG**