

# **EPIC® H-B 10 TBF-LB**

Housing design H-B. The industry standard.

The robust low metal housing with a direct cable entry is ideal for use in the plastics industry.

### Info

Single Lever version for quick locking and simple unlocking with lifting aid Protection rating UL50E tested







Supplementary automation components from Lapp



Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

### **Benefits**

The smallest housing with single and double lever. The right housing is available for every application

## **Application range**

Plant engineering Light & sound technology Plastics industry

# Product features

Cable coupler hood, low version

Last Update (02.10.2021)
©2021 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02\_03.16



# **EPIC® H-B 10 TBF-LB**

Single lever Straight cable entry Versions with / without neck

**Technical Data** 

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range: -40°C to +100°C, short-term up to +125°C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



# EPIC® H-B 10 TBF-LB

Article number	Article description	М	PG	Neck	Pieces / PU
H-B housing: cable coupler hood (1 straight cable entry, single lever)					
10046900	H-B 10 TBF-LB 16	-	16	yes	10
70042200	H-B 10 TBF-LB 21	-	21	yes	10
19046900	H-B 10 TBF-LB M20	20	-	-	10
79042200	H-B 10 TBF-LB M25	25	-	-	10