

Wireless Switch

8 buttons, white



Wireless remote control for scenes, lighting, heating, alarm modes or other home automation

Production data

- El-number (NO): 4512804
- Product category: Wireless Control
- SKU/Art.no: HC-BPW8-1
- GTIN (EAN): 7090026461124

Power

- Primary power source: Battery
- Voltage (V): DC 3 V
- Batteries included
- Type of batteries: CR2450
- No. of batteries required: 1
- Avg. battery life span: 12 (months)
- Low battery notification

Communication smart home

- · Requires smart home hub
- RF communication protocol: Zigbee 3.0
- Max wireless range (meter): 30
- OTA update support
- App control
- Name of available app(s): Heimgard app

Function keys

- Qty: 8
- Type: Select

Materials and colors

- Finish: Plastic
- · Color: White

Type of Keypad

Physical

Communication network

· No subscription required

Certificates

• CE

Key features

- 8 individual buttons
- Wireless home automation
- Battery operated
- Fits in to traditional combination frames
- Easy DIY installation

Order no.: 120908



Wireless Switch

8 buttons, white

Placement and operation temperature

- · Field of application: Indoors
- IP classification: IP20
- Operating temperature (°C): -10 +40
- Operating relative humidity (%): 40~90%RH (No condensation)
- · Mounting options: Double-sided tape
- · Placement: Wall
- · No authorized installer required
- · Type of junction box: Single
- Integration depth (mm): 0

Package Content

- · Main product
- · Mounting kit
- Quick start guide
 Icon sticker sheet

Design, dimensions and weight

- Dimensions HxWxD (mm): 8x8x1.5
- Net weight (g) F-PAK: 70
- Net weight per unit (g): 70

Logistics and packaging

- Customs Tariff Number (HS-Code): 8536.50.0000
- · Country of origin: China
- Dimensions F-PAK HxWxD (cm): 11.6x11x3,5
- Dimensions D-PAK HxWxD (cm): 36,5x35x35
- Gross weight F-PAK (g): 0.164
- Gross weight D-PAK(kg): 16
- Quantity in F-PAK (sales pack): 1
- · Number of F-PAK in D-PAK (carton): 90
- Minimum order quantity: 90
- Order multiple: 90
- Storage temperature (°C): 10-35°C
- Storage humidity (%): 30-50%RH (No condensation)

Safety

- · Protection class III
- Halogen-free

