

# Wireless Switch

4 buttons, black



Wireless remote control for scenes, lighting, heating, alarm modes or other home automation

#### Key features Production data Communication smart home • El-number (NO): 4512807 · Requires smart home hub 4 individual buttons · Product category: Wireless Control • RF communication protocol: Zigbee 3.0 Wireless home automation • SKU/Art.no: HC-BPB4-1 • Max wireless range (meter): 30 **Battery operated** • GTIN (EAN): 7090026461308 · OTA update support Fits in to traditional combination · App control Power frames · Name of available app(s): Heimgard app Easy DIY installation · Primary power source: Battery Function keys · Voltage (V): DC 3 V · Batteries included • Qty: 4 · Type: Select • Type of batteries: CR2450 Materials and colors · No. of batteries required: 1 • Avg. battery life span: 12 (months) · Finish: Plastic · Color:Black Low battery notification Type of Keypad Physical Communication network · No subscription required Certificates • CE Order no.: 120904



# Wireless Switch

## 4 buttons, black

#### Placement and operation temperature

- · Field of application: Indoors
- IP classification: IP20
- Operating temperature (°C): -10 +40
- Operating relative humidity (%): 40~90%RH (No condensation)
- · Mounting options: Double-sided tape
- · Placement: Wall
- · No authorized installer required
- · Type of junction box: Single
- Integration depth (mm): 0

### Package Content

- Main product
- · Mounting kit
- Quick start guide
- · Icon sticker sheet

### Design, dimensions and weight

- Dimensions HxWxD (mm): 8x8x1.5
- Net weight (g) F-PAK: 70
- Net weight per unit (g): 70

#### Logistics and packaging

- Customs Tariff Number (HS-Code): 8536.50.0000
- · Country of origin: China
- Dimensions F-PAK HxWxD (cm): 11.6x11x3,5
- Dimensions D-PAK HxWxD (cm): 36,5x35x35
- Gross weight F-PAK (g): 0.164
- Gross weight D-PAK(kg): 16
- Quantity in F-PAK (sales pack): 1
- · Number of F-PAK in D-PAK (carton): 90
- Minimum order quantity: 90
- Order multiple: 90
- Storage temperature (°C): 10-35°C
- Storage humidity (%): 30-50%RH (No condensation)

#### Safety

- · Protection class III
- · Halogen-free

