

Products → Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → Kabeldon IP-System

General Information

Global Commercial Alias:	6303.0038.0
Extended Product Type:	AD 70
Product ID:	2CGX063030038
EAN:	7331980003709
Catalog Description:	AD 70 Non-insulated connector
Long Description:	Non insulated connector, only to be used with non-protected busbars

Ordering

EAN:	7331980003709
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369010

Dimensions

Product Net Width:	23 mm
Product Net Height:	45 mm
Product Net Depth:	33 mm
Product Net Weight:	0,1 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	85 mm
Package Level 1 Height:	39 mm
Package Level 1 Length:	10 mm
Package Level 1 Gross Weight:	0,1 kg
Package Level 1 EAN:	7331980003709
Package Level 2 Units:	50 piece
Package Level 2 Width:	160 mm
Package Level 2 Height:	110 mm
Package Level 2 Length:	170 mm
Package Level 2 Gross Weight:	6,511 kg
Product Packing Type:	Box

Additional Information

Cable Cross-Section:	6 ... 95 mm ²
-----------------------------	--------------------------

Conventional Thermal Current (I_{the}):	200 A
Degree of Protection:	acc. to IEC 60529 IP00
Product Main Type:	Connector
Product Name:	Non-insulated connector
Rated Operational Current (I_e):	200 A
Rated Operational Voltage:	690 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 19 kiloampere rms
Suitable For:	Kabeldon busbar
Tightening Torque:	20 N·m Wire-Clamp 10 ... 20 N·m

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CGC0036
Declaration of Conformity - CE:	2CGC0021
Instructions and Manuals:	4390145921

Classifications

E-number:	0732601
ETIM 5:	EC000001 - Busbar terminal
ETIM 6:	EC000001 - Busbar terminal

