

Products → Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → Kabeldon IP-System

General Information

Global Commercial Alias:	6303.0195.0
Extended Product Type:	AD 300
Product ID:	2CGX063030195
EAN:	7331980003730
Catalog Description:	AD 300 Insulated connector
Long Description:	Insulated connector

Ordering

EAN:	7331980003730
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369010

Dimensions

Product Net Width:	38 mm
Product Net Height:	100 mm
Product Net Depth:	79 mm
Product Net Weight:	0,2 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	100 mm
Package Level 1 Height:	35 mm
Package Level 1 Length:	100 mm
Package Level 1 Gross Weight:	0,2 kg
Package Level 1 EAN:	7331980003730
Package Level 2 Units:	50 piece
Package Level 2 Width:	210 mm
Package Level 2 Height:	195 mm
Package Level 2 Length:	520 mm
Package Level 2 Gross Weight:	10 kg
Product Packing Type:	Box

Additional Information

Cable Cross-Section:	50 ... 300 mm ²
-----------------------------	----------------------------

Conventional Thermal Current (I_{the}):	630 A
Degree of Protection:	acc. to IEC 60529 IP2X
Product Main Type:	Connector
Product Name:	Insulated connector
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current (I_e):	630 A
Rated Operational Voltage:	690 V
Suitable For:	Kabeldon busbar
Tightening Torque:	20 N·m Wire-Clamp 20 ... 45 N·m

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CGC0036
Declaration of Conformity - CE:	2CGC0021
Instructions and Manuals:	9AKK107045A3939

Classifications

E-nummer:	0732605
ETIM 5:	EC000001 - Busbar terminal
ETIM 6:	EC000001 - Busbar terminal

