

Products → Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → Kabeldon IP-System

General Information

| | |
|---------------------------------|--|
| Global Commercial Alias: | 6305.0107.1 |
| Extended Product Type: | SLD 00 |
| Product ID: | 2CGX063050107 |
| EAN: | 7331980032402 |
| Catalog Description: | SLD 00 Fuse switch disconnecter |
| Long Description: | Fuse switch disconnecter with dependent manual operation |

Ordering

| | |
|--------------------------------|---------------|
| EAN: | 7331980032402 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85369010 |

Dimensions

| | |
|----------------------------|--------|
| Product Net Width: | 50 mm |
| Product Net Height: | 495 mm |
| Product Net Depth: | 160 mm |
| Product Net Weight: | 1,8 kg |

Container Information

| | |
|--------------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 160 mm |
| Package Level 1 Height: | 50 mm |
| Package Level 1 Length: | 495 mm |
| Package Level 1 Gross Weight: | 1,8 kg |
| Package Level 1 EAN: | 7331980032402 |
| Package Level 2 Units: | 80 piece |
| Package Level 2 Width: | 800 mm |
| Package Level 2 Height: | 750 mm |
| Package Level 2 Length: | 1200 mm |
| Package Level 2 Gross Weight: | 144 kg |
| Product Packing Type: | Pallet |

Additional Information

| | |
|-----------------------------|----------------------------|
| Cable Cross-Section: | 2.5 ... 95 mm ² |
| Connection Type: | Screw clamp |

| | |
|--|------------------------------------|
| Conventional Thermal Current (I_{the}): | 160 A |
| Degree of Protection: | acc. to IEC 60529 IP2X |
| Fuse Size: | 00 |
| Fuse Type: | NH |
| Handle Type: | Cover grip |
| Number of Poles: | 3 |
| Product Main Type: | Switching device |
| Product Name: | Fuse switch disconnecter |
| Rated Impulse Withstand Voltage (U_{imp}): | 8 kV |
| Rated Insulation Voltage (U_i): | 690 V |
| Rated Operational Current (I_e): | 160 A |
| Rated Operational Current AC-21B (I_e): | (690 V) 160 A |
| Rated Operational Current AC-23B (I_e): | (400V) 160 A |
| Rated Operational Voltage: | 400 V |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 6.1 kiloampere rms |
| Tightening Torque: | 15 N·m Wire-Clamp 15 ... 20 N·m |

Certificates and Declarations (Document Number)

| | |
|---|------------|
| Data Sheet, Technical Information: | 2CGC0036 |
| Declaration of Conformity - CE: | 2CGC0023 |
| Environmental Information: | 2CGC0033 |
| Instructions and Manuals: | 439075291B |

Classifications

| | |
|------------------|-------------------------------------|
| E-nummer: | 0732749 |
| ETIM 5: | EC001040 - Fuse switch disconnecter |
| ETIM 6: | EC001040 - Fuse switch disconnecter |

