




# Single Pole Distribution Block – UD6C500AL (569201)



- Tinned copper or aluminum block allows for copper or aluminum conductor direct connections, or using ferrule
- Screw retaining cover is hinged and removable
- Design allows for visual inspection of conductor and confirmation of connection
- Modular snap-together blocks for building multi-pole power blocks
- Easily clips onto DIN rail or mounts to panel with screws
- 95% fill ratio
- Halogen free
- RoHS compliant



Part Number	UD6C500AL
Article Number	569201
Finish	Tinned
Max Current Rating, IEC	500 A
Max Current Rating, UL/CSA	380 A
Line Side Connection	Cable
Load Side Connection	6 Cables
Material	Aluminum Thermoplastic
Line Side Max Conductor Size, IEC	240 mm <sup>2</sup>
Load Side Max Conductor Size, IEC	50 mm <sup>2</sup>
Max Working Voltage, IEC (Ui)	1,000 VAC 1,500 VDC
Max Working Voltage, UL (Vin)	1,000 VAC/DC
Short Term Withstand Current (Icw) 1s	34.3 kA
Peak Short Circuit Current (Ipk)	52.5 kA
Short Circuit Current Rating (SCCR)	100 kA
Line Side Number of Connections	1
Line Side Compact Stranded Wire Size	95 - 240 mm <sup>2</sup>
Line Side Wire Size	3/0 - 500 kcmil
Load Side Number of Connections	6
Load Side Compact Stranded Wire Size	10 - 50 mm <sup>2</sup>

Part Number	UD6C500AL
Load Side Stranded Wire Size - Ferrule	#8 - #1
Load Side Wire Size	#8 - 1/0
Enclosure Rating	IP 20
Depth	148.1 mm
Height	90.2 mm
Width	43.7 mm
Unit Weight	0.34 kg
Certification Details	UL® 1953
Flammability Rating	UL® 94V-0
Complies With	IEC® 60947-7-1
Certifications	UL
Standard Packaging Quantity	1 pc
UPC	78285697535
EAN-13	0782856975359

Design Guideline for Distribution Blocks, Power Blocks and Power Terminals										
Derating according to Ambient* Temperature [°C] to maintain working temperature of 85°C										
Ambient Temperature [°C]	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°
Derating Coefficient (d)	1	1	1	0.94	0.88	0.82	0.75	0.67	0.58	0.47
*environment around the terminal blocks inside the enclosure										

Increase the number of outputs with one input using a jumper on blocks with a Max Current Rating, IEC up to 160 A.  
 Blocks with 1,000 VAC/DC Max Working Voltage, UL are ideal for solar applications.

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cULus and cURus are registered certification marks of UL LLC.

**WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.