



Cable to Cable Power Block – SB125AL (561161)



- Compact power block with high short circuit current rating
- Tinned copper or aluminum block allows for copper or aluminum conductor connections
- Screw retaining cover is hinged and removable
- Design allows for visual inspection of conductor and confirmation of connection
- Gangable for building multi-pole power blocks
- Easily clips onto DIN rail or mounts to panel with screws
- 95% fill ratio
- Halogen free
- RoHS compliant



Part Number	SB125AL
Article Number	561161
Material	Aluminum Thermoplastic
Finish	Tinned
Max Current Rating, IEC	185 A
Max Current Rating, UL/CSA	150 A
Peak Short Circuit Current (I _{pk})	22 kA
Short Circuit Current Rating (SCCR)	100 kA
Max Working Voltage, IEC (U _i)	1,000 VAC 1,500 VDC
Max Working Voltage, UL (V _{in})	1,250 VAC/DC
Line Side Number of Connections	1
Line Side Compact Stranded Wire Size	10 - 35 mm ² #8 - 1/0
Load Side Number of Connections	1
Load Side Compact Stranded Wire Size	10 - 35 mm ² #8 - 1/0
Load Side Stranded Wire Size - Ferrule	10 - 35 mm ²
Enclosure Rating	IP 20
Depth (D)	46.9 mm
Height (H)	84 mm

Part Number	SB125AL
Width (W)	20.2 mm
Unit Weight	0.045 kg
Certification Details	UL® 1059
Flammability Rating	UL® 94V-0
Complies With	IEC® 60947-7-1
Certifications	CE cURus RoHS
Standard Packaging Quantity	1 pc
UPC	78285691267
EAN-13	8711893155167

Design Guideline for Distribution Blocks, Power Blocks and Power Terminals										
Derating according to Ambient* Temperature (°C) to maintain working temperature of 85°C										
Ambient Temperature (°C)	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°
Derating Coefficient (d)	1	1	1	0.94	0.88	0.82	0.75	0.67	0.58	0.47
*environment around the terminal blocks inside the enclosure										

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.