


ISO-TP Low Voltage Male/Female Insulators – ISOTP80F8M8 (542110)



- Halogen free
- High resistance to leakage current
- Great stability of electrical and mechanical parameters
- Fiberglass reinforced
- UL® Recognized in E125470 and evaluated for dielectric withstand rating of 1,500 VAC/DC
- RoHS compliant



Part Number	ISOTP80F8M8
Article Number	542110
Material	Glass Fibre Reinforced Polyamide Steel
Finish	Electrogalvanized
Working Temperature	-40 to 130 °C
Insulation Voltage	1,000 VAC 1,500 VDC
Flammability Rating	UL® 94V-0
Height (H)	80 mm
Hex Width (W)	65 mm
Depth (D)	75 mm
Diameter (Ø)	52 mm
Thread Size 1 (TS1)	M8
Thread Length (TL)	17 mm
Thread Size 2 (TS2)	M8
Thread Depth (TD)	15 mm
Static Load 1 (F1)	22,000 N
Static Load 2 (F2)	10,000 N
Unit Weight	0.35 kg
Certifications	cURus RoHS

Part Number	ISOTP80F8M8
Standard Packaging Quantity	10 pc
UPC	78285687519
EAN-13	3479775421100

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.