



Data subject to change without notice. Always confirm the data is correct from the seller.

KEM 325U/EMC

EMC Switches 10-630A

- Electromagnetic compatibility ensures safe operation in environments with electromagnetic disturbance
- Tested according to EMC EN 61000-6-3:2007+A1(2011) with EMC-glands shielded power cable
- IP66; Enclosure types U2, U3, A2, A3
- IP65; Enclosure types TR02, TR03, TR04
- Available in polycarbonate up to 125 A, aluminium up to 160 A and sheet steel up to 630 A
- Also available in TR02, TR03 and TR04 enclosures
- Padlockable
- EMC cable glands included
- Door interlock with defeat mechanism
- Tested according to IEC 60947-3
- Also available with 4, 6 or 8-poles
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here**.

[Technical datasheet >>](#)

Accessories



Product details

| | |
|---|-------------------|
| SKU | KEM 325U/EMC |
| AC-21 400/415 V (A) | 40 A |
| AC-21 690 V (A) | 40 A |
| AC-22 400/415 V (A) | 25 A |
| AC-22 690 V (A) | 25 A |
| AC-23 400/415 V (A/kW) | 25 A / 11 kW |
| AC-23 690 V (A/kW) | 25 A / 22 kW |
| Cable Area to Switch Terminal (mm²) / Bolt size | 1.5-16 |
| Cable Gland | 2xM25 |
| Color | Standard |
| EAN | 6419410329214 |
| Enclosure | U2 |
| Enclosure Type | Polycarbonate |
| IP Rating | 66 |
| Number of Poles | 3 |
| Operation | Front-operated |
| Switch type | Load Break Switch |
| Weight (kg) | 0.6 |

Dimensional drawing

