



JUNCTION BOX

**WK 007-2,5<sup>2</sup>**



**WK 007-2,5<sup>2</sup>**

**Junction box**

80 x 80 x 38 mm

Article number: 40240701

Junction box acc. DIN EN 60670 (VDE 0606), Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M16, seal range 6 - 10 mm

grey, with screw terminal 5-poles - 2.5 mm<sup>2</sup>, (6 x 1.5<sup>2</sup> / 4 x 2.5<sup>2</sup>)



**Technical data**

**Measures**

Width:	80 mm
Length:	80 mm
Height:	38 mm

**Material**

Base:	Duroplastic
Cover:	Duroplastic
Sealing:	thermoplastic elastomer
Cover screw:	Steel

**Other attributes**

Entries:	7
Rated cross section:	2,5 mm <sup>2</sup>
Tackable:	No
Rated insulation voltage AC:	400 V

**Accessory**

KVR M16-MGM
AST M16
KVR M16
GMU PA M16
ADR M16
WST M16
WNI M16
VST M16
VSS PA M16
RST M16
WK 007 KLS-2,5 <sup>2</sup>
WST M16/sw
WNI M16/sw
DMS M16
MPS-KRI
KVR M16-MGM
AST M16



JUNCTION BOX

**WK 007-2,5<sup>2</sup>**

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP54 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equipment:	Terminal
Color:	grey

KVR M16
GMU PA M16
ADR M16
WST M16
WNI M16
VST M16
VSS PA M16
RST M16
WK 007 KLS-2,5 <sup>2</sup>
WST M16/sw
WNI M16/sw
DMS M16
MPS-KRI

**Environmental attributes**

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%