



JUNCTION BOX

**WK 250-25<sup>2</sup>**

**WK 250-25<sup>2</sup>**

**Junction box**

256 x 171 x 106 mm

Article number: 42541601

Junction box acc. DIN EN 60670 (VDE 0606), Ui=690V, Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M40, seal range 17 - 30 mm, with sealing kit

grey, with screw terminal 5-poles - 25 mm<sup>2</sup>, (5 x 16<sup>2</sup> / 3 x 25<sup>2</sup>)



**Technical data**

**Measures**

Width:	256 mm
Length:	171 mm
Height:	106 mm

**Material**

Base:	Duroplastic
Cover:	Duroplastic
Sealing:	thermoplastic elastomer
Cover screw:	Steel

**Other attributes**

Entries:	16
Rated cross section:	25 mm <sup>2</sup>
Tackable:	No
Rated insulation voltage AC:	690 V

**Accessory**

- KVR M40-MGM
- VST M40-or
- AST M40-or
- AST M40
- WK 250 KLS-25<sup>2</sup>
- KVR M40
- GMU PA M40
- ADR M40
- WST M40
- VST M40
- SNI M40
- KS M40
- KVR M40-MGM/sw
- KVR M40-MGM
- VST M40-or
- AST M40-or
- AST M40



JUNCTION BOX

**WK 250-25<sup>2</sup>**

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP54 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equipment:	Terminal
Color:	grey

WK 250 KLS-25<sup>2</sup>

KVR M40

GMU PA M40

ADR M40

WST M40

VST M40

SNI M40

KS M40

KVR M40-MGM/sw

**Environmental attributes**

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%