R305887

966733705





010.2175

SCOPE OF SUPPLY

- 19" 1U 16-port patch panel, empty, shielded
- 16 Cat. 6 connection modules, RJ45/s incl. EMC covers and dust covers
- 19" mounting kit
- 3 jumpering brackets
- 4 labeling strips
- Cable ties
- Installation instructions

TENDER

RJ45 connection module of Category 6, for the setting up of transmission channels of class E and class EA (and Cat. 6/Cat. 6A) with up to 4 plugged connections, and class F on 2 pairs, complies with Category 6 requirements of the standards ISO/ IEC 11801, EN 50173-1, (DIN EN 50173-1) as well as TIA/EIA 568.2-D, de-embedded tested in acc. with IEC 60603-7-5, interoperable and backwards compatible with Category 5e and Category 5.

Suitable for 10GBASE-T applications in acc. with IEEE 802.3[™] Section Four up to 500 MHz and 100 m.

Tested on the basis of the R&M production control including 100%.

Compatible with RJ standard plugs (RJ11, RJ12, RJ45), PCB-free and tool-free Easy-Lock connection of installation cables AWG 26 22 (0.4 mm 0.65 mm) and flexible cables AWG 26/7 AWG 22/7. Parallel pair termination without crossover in acc. with TIA 568-A/B, gold-plated bronze contacts for >1000 mating cycles, IDC contacts with single-wire strain relief and >20 insertion cycles, contact resistance <50 mOhm, dielectric strength >1000 Veff. PoE and PoE+ compatible according to IEC 60512-99-001. Shield contacting by patented shield lance with integral cable strain relief, shield material tin-coated bronze, ground contacting through 2 contact fingers for flat connectors 4.8 x 0.5 mm.

Material: halogen-free and heavy-metal free in acc. with EU directives RoHS 2.

Connection module Cat. 6, shielded, with EMC cover, dust cover, mounting plate, cable tie and installation instructions.

TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Number of connectors (A)	16
Category connector (A)	Cat. 6
Connector type (A)	RJ45
Shielding connector (A)	shielded
PoE	Yes
Amount of height units	1 U

Rack mounting version Assembly Holder for connector / module	patch panel fully populated Mounting plate
Capacity (ports)	16
Standard	IEC 60603-7: Electrical Characteristics of the Telecommunication Outlets EN 50173-1
	ISO/IEC 11801
Amount of height units	1 U
Fastening	19 " U

MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Dimensions	482.2 mm x 43.2 mm x 106.0 mm / 18.984 in x 1.701 in x 4.173 in (W x H x D)
Color Code NCS	S 2502-B
Material	plastic: PC, fiber-glass reinforced

ACCESSORIES

Туре	Picture	Description	Article	E-Number
Optional accessories	r 🖗 🌳	Plug Guard RJ45, green	R304825	977901245
Optional accessories	🖗 🏟 🏟	Plug Guard RJ45, red	R304826	977901265
Optional accessories	r 🖗 🏟	Plug Guard RJ45, white	R304827	977901215
Optional accessories	m m m	Hinged Dust Cover, anthracite	R305685	977901405
Optional accessories	M M M	Hinged Dust Cover, blue	R305686	977901425
Optional accessories	M M M	Hinged Dust Cover, brown	R305687	977901485
Optional accessories		Hinged Dust Cover, yellow	R305688	977901455
Optional accessories	M M M	Hinged Dust Cover, gray	R305689	977901555
Optional accessories	M C C C	Hinged Dust Cover, green	R305690	977901445
Optional accessories	M Com	Hinged Dust Cover, red	R305691	977901465
Optional accessories	r n	Hinged Dust Cover, violet	R305692	977901435

Туре	Picture	Description	Article	E-Number
Optional accessories	Co Co Co	Hinged Dust Cover, white	R305693	977901415
Optional accessories		Labeling Sheet to 16-Port Patch Panel	R306039	977939005
Optional accessories	0	Splash Cap IP54, blue	R306058	966907125
Optional accessories	C	Splash Cap IP54, yellow	R306060	966907155
Optional accessories	0	Splash Cap IP54, green	R306061	966907145
Optional accessories	C	Splash Cap IP54, red	R306062	966907165
Optional accessories	210	Splash Cap IP54, white	R306063	966907115
Optional accessories	0000	19" 1U Cable Management Plastic, 70 m	nmR306179	966930015
Optional accessories	200	19" 2U Cable Management Plastic, 70 m	nmR306180	966930025
Optional accessories	30	19" Lateral Radius Guard, left and right	R306181	
Optional accessories		Plug Reduction Frame RJ45 onto RJ11/	R R310835	977990705