



DESCRIPTION

- Protection class IP67 according to IEC 60529
- Suitable for protective housing variant 06

090.2124

SCOPE OF SUPPLY

- Mounting frame IP67 type06
- Gasket
- 4 screws M3x10
- 4 nuts M3

TENDER

Mounting frame Interbus designed for round mounting cutouts. Suitable for protective housing for field terminatable RJ45 plug with snap latch. Protection class IP67 according to IEC60529. Accommodates optional color coding. Polyamide, traffic gray (RAL 7042). Including gasket and screws M3 x 10mm.

TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Colour Coding	Yes, optional
UL Classification	UL94-V0
Standard	IEC 60529-6


MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Dimensions	36.0 mm x 36.0 mm x 27.5 mm / 1.417 in x 1.417 in x 1.083 in (W x H x D)
Color Code RAL	7042 Traffic gray A
Material	PA (polyamide)

ENVIRONMENTAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Operation temperature	-40 °C to +80 °C / -40 °F to +176 °F

ACCESSORIES

Type	Picture	Description	Article	E-Number
Optional accessories		Protection Cap FM45 IP67 Type06 frame	R309589	977891395