19" 3U Global Patch Panel 60-Port/s, empty

966730485



DESCRIPTION

Holds up to fifteen Global/s connection module holders, Global blind covers or six Global adapter units. Max. capacity of 60 RJ45/s connection modules.

010.2054

SCOPE OF SUPPLY

- 19" 3U Global patch panel/s incl. cable tie shelf
- · Grounding system
- 19" mounting kit
- Installation instructions

TENDER

Modular patch panel accommodating up to fifteen connection module holders Global/s, installation-friendly thanks to snapand-go technique, featuring a complete grounding system and Global blind cover. Designed to accommodate the R&M security and the R&M environment system, with its 3-level protection concept: color coding, mechanical coding, locking option. Exchangeable labeling strips, integral cable tie shelf, fastening kit, labeling fields, tool-free locking and unlocking system. Automatic ground contacting by spring contacts. Profile aluminum, colorless chromatized; cable tie shelf sheet steel (DC01A) 1.5 mm, color blue passivated; side panel plastic (PA), fiberglass-reinforced, halogen-free, color medium gray (NCS 2502-B).

With a capacity of up to 60 shielded RJ45 connection modules of Category 5, class D, Category 6, class E and Real10 Category 6, class E and class EA for the establishing of transmission channels with up to 4 plugged connections or 15 FiberModuls 5.6HP, splice or breakout version, for 60 E-2000[™] Compact or SC-RJ adapters.

TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Connector type (A)	RJ45
Shielding connector (A)	shielded
PoE	Yes
Amount of height units	3 U
Rack mounting version	patch panel
Assembly	empty
Capacity (ports)	60
Standard	UL Listed
Amount of height units	3 U
Fastening	19 " U
MECHANICAL DATA	
DESCRIPTION	VALUE / VALUE RANGE
Dimensions	482.6 mm x 132.5 mm x 221.0 mm / 19 in x 5.217 in x 8.701 in (W x H x D)

Color Code NCS
Material

S 2502-B

steel: DC01 (1.0330), 1.5 mm / aluminum / plastic: PA66, fiber-glass reinforced, halogen-free

ACCESSORIES

Туре	Picture	Description	Article	E-Number
Optional accessories	1	Blind Cover 3U Global, 1 GU	R35401	966730335
Optional accessories		Connection Module Holder 3U Global/s,	1 R35402	966730455
Optional accessories		Voice Adapter 3U Global, 3x10-Port, 3 C	G R310400	977833305