

DESCRIPTION

Holds up to sixteen 2U Global/s connection module holders or 2U Global blind covers. Max. capacity of 48 RJ45/s connection modules.



090.3101

SCOPE OF SUPPLY

- 19" 2U Global patch panel/s
- Grounding system
- 19" mounting kit
- Installation instructions

TENDER

Modular patch panel accommodating up to sixteen connection module holders 2U Global/s, installation-friendly thanks to snap-and-go technique, featuring a complete grounding system and 2U Global blind cover. Designed to accommodate the R&M security and the R&M environment system, with its 3-level protection concept: color coding, mechanical coding, locking option. Exchangeable labeling strips, fastening kit, labeling fields, tool-free locking and unlocking system. Automatic ground contacting by spring contacts. Profile aluminum, colorless chromated; side panel plastic (PC), fiberglass-reinforced, halogen-free, color medium gray (NCS 2502-B).

With a capacity of up to 48 shielded RJ45 connection modules of Category 5, class D, Category 6, class E and Real10 Category 6, class E and class EA for the establishing of transmission channels with up to 4 plugged connections.



TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
PoE	Yes
Amount of height units	2 U
Rack mounting version	patch panel
Assembly	empty
Capacity (ports)	48
Standard	UL Listed
Amount of height units	2 U
Fastening	19 " U

MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Dimensions	482.6 mm x 88.1 mm x 82.0 mm / 19 in x 3.468 in x 3.228 in (W x H x D)
Color Code NCS	S 2502-B
Material	aluminum / plastic: PC, fiber-glass reinforced, halogen-free

ACCESSORIES

Type	Picture	Description	Article	E-Number
Optional accessories		Blind Cover 2U Global	R316871	966733295
Optional accessories		Connection Module Holder 2U Global/s	R503813	966733275