19" 1U ST Patch Panel 24xRJ45/s, Cat. 6A, gray, fully populated

966733625



090.5365

SCOPE OF SUPPLY

- 19" 1U 24-port metal patch panel, empty, integrated cable tie shelf
- 24 Cat. 6A ISO connection modules, RJ45/s incl. EMC covers and dust covers
- 19" mounting kit
- 4 labeling strips
- Cable ties
- Installation instructions

TENDER

Patch panel with integrated cable tie shelf, optional direct grounding, 19" fastening kit, labeling field, accepting the snap-in type color coding clips in 8 colors.

Material: sub-rack made of sheet steel (DC01A) 1.5 mm, color blue chromatized, screen made of plastic (ABS), halogen-free, color medium gray (NCS 2502-B).

RJ45 connection module of Cat. 6A ISO, for the setting up of transmission channels of Class EA with up to 4 plugged connections acc. to ISO/IEC 11801, EN 50173-1, (DIN EN 50173-1) and Class F on 2 pairs, complies with Cat. 6A requirements of the standards ISO/IEC 11801, EN 50173-1, as well the U.S. standard Cat. 6A according to TIA/EIA 568.2-D, re-embedded tested in acc. with IEC 60603-7-51 and 60512-27-100, interoperable and backwards compatible with Category 6 and Category 5e.

Suitable for 10GBASE-T applications in acc. with IEEE 802.3[™] Section Four up to 500 MHz and 100 m.

Tested in line with R&M's manufacturing control, performing 100% inspection.

Compatible with RJ standard plugs (RJ11, RJ12, RJ45), connection with automatic wire cutting of installation cables AWG 26 22 (0.4 mm 0.65 mm) and flexible cables AWG 26/7 AWG 22/7 without special tools. X-Separator for individual pair shielding. Parallel pair termination without crossover in acc. with TIA 568-A/B, gold-plated bronze contacts for >1000 mating cycles, IDC contacts with >20 insertion cycles, contact resistance <5 mOhm, dielectric strength >1000 Veff. Supports PoE (IEEE 802.3af), PoEP (IEEE 802.3at), 4PpoE (IEEE 802.3bt) and is compatible to IEC 60512-99-001/002. 90° wire orientation without bending cable. With integral cable strain relief, including dust cover. Shield contacting by patented shield lance with integral cable strain relief, shield material tin-coated bronze, ground contacting through 1 contact finger for flat connectors 4.8 x 0.5 mm.

Material: halogen-free and heavy-metal free in acc. with EU directives RoHS 2.

Connection module Cat. 6A ISO, shielded, with EMC cover, dust cover, snap-in frame (gray), cable tie and installation instructions.

TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Number of connectors (A)	24
Category connector (A)	Cat. 6A ISO

Connector type (A)	RJ45
Shielding connector (A)	shielded
PoE	Yes
Amount of height units	1 U
Rack mounting version	patch panel
Assembly	fully populated
Holder for connector / module	Snap-in frame
Capacity (ports)	24
Standard	EN 50173-1
	IEC 60603-7-51: Electrical Characteristics of the Telecommunication Outlets ISO/IEC 11801
Amount of height units	Telecommunication Outlets
Amount of height units Fastening	Telecommunication Outlets ISO/IEC 11801
-	Telecommunication Outlets ISO/IEC 11801 1 U
Fastening	Telecommunication Outlets ISO/IEC 11801 1 U
Fastening MECHANICAL DATA	Telecommunication Outlets ISO/IEC 11801 1 U 19 " U

steel: DC01 (1.0330), 1.5 mm

Material

ACCESSORIES

Туре	Picture	Description	Article	E-Number
Optional accessories		Protective Conductor Terminal 6 mm ²	R302150	970502005
Optional accessories		Snap-in Coding Clip, anthracite	R302151	977907005
Optional accessories		Snap-in Coding Clip, blue	R302152	977907025
Optional accessories		Snap-in Coding Clip, brown	R302153	977907085
Optional accessories		Snap-in Coding Clip, green	R302154	977907045
Optional accessories		Snap-in Coding Clip, red	R302155	977907065
Optional accessories		Snap-in Coding Clip, violet	R302156	977907035
Optional accessories		Snap-in Coding Clip, white	R302157	977907015
Optional accessories		Snap-in Coding Clip, yellow	R302158	977907055

Туре	Picture	Description	Article	E-Number
Optional accessories		Labeling Sheet 24-Port ST Patch Panel	R305090	973806635
Optional accessories	0000	19" 1U Cable Management Plastic, 70 m	nmR306179	966930015
Optional accessories	20	19" 2U Cable Management Plastic, 70 m	nmR306180	966930025
Optional accessories	30	19" Lateral Radius Guard, left and right	R306181	
Optional accessories		Snap-in Blind Cover, light gray	R308708	977904135