

DESCRIPTION



090.7758

SCOPE OF SUPPLY

- 19" 1U slide-in unit, fastening material, labeling strips and installation instructions
- One 2 x 15 mm radius guards
- Fastening strap for safe cable fixation
- Front panel equipped with adapters

TENDER

- Delta insertion loss: ≤ 0.2 dB, testing method acc. to IEC 61300-3-4
- Mating cycles: min. 500
- Pull-out force: min. 70 N (per connector)









TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Fiber type	Multimode (MM)
Number of connectors (A)	12
Connector type (A)	SC-Duplex
Connector color (A)	beige
Polishing plug (A)	PC
Protection class IP (A)	IP 20
Attenuation grade IL (A)	M
Amount of height units	1 U
Rack mounting version	patch panel
Adapter fastening method	end cap snap-in
Assembly	partly populated
Capacity (ports)	24
Sleeve material	ceramic
Version	breakout
Standard	IEC 60297-3: 19-inch (482.6 mm) rack Adapter in acc. with IEC 61754-4
Amount of height units	1 U

MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Dimensions	43.6 mm x 482.6 mm x 225.0 mm / 1.717 in x 19 in x 8.858 in (W x H x D)
Color Code NCS	S 2502-B
Material	steel: DC01 (1.0330), 1.0 mm

ACCESSORIES

Type	Picture	Description	Article	E-Number
Optional accessories		Patching Ring left / right, 35 mm, gray	R302004	973453825
Optional accessories		Patching Ring left / right, 75 mm, gray	R302005	966791005
Optional accessories		Fibereasy Breakout Kit	R303577	
Optional accessories		Patching Ring FOM left / right, 75 mm, gr	R304440	966791105
Optional accessories		21" 1U Adapter Kit UniRack	R305148	
Optional accessories		Breakout Cable SC PC 24x - SC PC 24x, R502234		
Optional accessories		Breakout Cable SC PC 24x - SC PC 24x, R502237		
Optional accessories		Breakout Cable SC PC 24x - SC PC 24x, R502241		