

19" 1U FibereasyRack2 24xLC-Duplex singlemode, PC, ceramic, R&MinteliPhy ready

DESCRIPTION

Special mounting brackets for mounting the R&MinteliPhy Sensorbar.



090.7557

SCOPE OF SUPPLY

- 19" 1U slide-in unit, fastening material, labeling strips and installation instructions
- One 2 x 15 mm radius guards
- Fastening strap for safe cable fixation
- Front panel equipped with adapters

TENDER

Breakout and patch box, mounting depth 225 mm, continuously depth-adjustable up to 55 mm, rear cable feed, cable entry possible from three different angles. The box units are on the same level, the storage part for pre-terminated cables features fastening strap, fitted with adapters; the box is continuously extendable up to 210 mm, at full extension it can be inclined 10° forwards. Optimum access to the pre-terminated cables, the tray can be fully detached from the box by release lever. Special mounting brackets for mounting the R&MinteliPhy Sensorbar. Includes indelible laser trademark, fastening material, labeling strips and installation instructions.

Features:

- Dimensions: 43.6 x 482.6 x 225 mm
- Material: box, powder-coated sheet steel / front panel, plastic PC, fiber-glass reinforced
- Color: medium gray (NCS 2502-B, approximating RAL 7035)
- Dimensions: 43.6 x 482.6 x 225 mm
- Material: box, powder-coated sheet steel / front panel, plastic PC, fiber-glass reinforced
- Color: medium gray (NCS 2502-B, approximating RAL 7035)
- Assembled with 24 x
- Delta insertion loss: ≤ 0.2 dB, testing method acc. to IEC 61300-3-4
- Mating cycles: min. 500
- Pull-out force: min. 70

TECHNICAL DATA










DESCRIPTION	VALUE / VALUE RANGE
Fiber type	Singlemode (SM)
Number of connectors (A)	24
Connector type (A)	LC-Duplex
Connector color (A)	blue
Polishing plug (A)	PC

Protection class IP (A)	IP 20
Attenuation grade IL (A)	C
Amount of height units	1 U
Rack mounting version	patch panel
Adapter fastening method	end cap snap-in
Assembly	fully populated
Capacity (ports)	24
Sleeve material	ceramic
Version	breakout
Standard	Adapter in acc. with IEC 61754-20 IEC 60297-3: 19-inch (482.6 mm) rack
Amount of height units	1 U
Fastening	19 " U

MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Dimensions	43.6 mm x 482.6 mm x 225.0 mm / 1.717 in x 19 in x 8.858 in (W x H x D)
Color Code NCS	S 2502-B
Material	steel: DC01 (1.0330), 1.0 mm

ACCESSORIES

Type	Picture	Description	Article	E-Number
Optional accessories		Patching Ring left / right, 35 mm, gray	R302004	973453825
Optional accessories		Patching Ring left / right, 75 mm, gray	R302005	966791005
Optional accessories		Fibereasy Breakout Kit	R303577	
Optional accessories		Patching Ring FOM left / right, 75 mm, gr	R304440	966791105
Optional accessories		21" 1U Adapter Kit UniRack	R305148	
Optional accessories		Breakout Cable LC PC 24x - LC PC 24x, R502271		
Optional accessories		Breakout Cable LC PC 24x - LC PC 24x, R502288		
Optional accessories		Breakout Cable LC PC 24x - LC PC 24x, R502290		
Optional accessories		Fibereasyrack 2-mounting plate-divider	R862117	