

1U-FiberRack2-24-scdzpcc-bl

DESCRIPTION



090.7314

SCOPE OF SUPPLY

- 19" 1U slide-in unit, splice tray plate with 2 splice trays radius 40 mm, fastening material, labeling strips and installation manual
- Front panel equipped with adapters and pigtails

TECHNICAL DATA

| DESCRIPTION | VALUE / VALUE RANGE |
|--------------------------|---|
| Conductor type FO | semi-tight buffer, dry |
| Number of connectors (A) | 24 |
| Connector type (A) | SC-Duplex |
| Polishing plug (A) | PC |
| Protection class IP (A) | IP 20 |
| Amount of height units | 1 U |
| Rack mounting version | patch panel |
| Adapter fastening method | end cap snap-in |
| Assembly | fully populated |
| Capacity (ports) | 24 |
| Sleeve material | ceramic |
| Version | splice |
| Standard | Adapter and connector in acc. with IEC 61754-4 Pigtails in acc. with color code DIN VDE 0888 IEC 60297-3: 19-inch (482.6 mm) rack |
| Amount of height units | 1 U |
| Fastening | 19 " U |

MECHANICAL DATA

| DESCRIPTION | VALUE / VALUE RANGE |
|----------------|---|
| Dimensions | 43.6 mm x 482.6 mm x 225.0 mm / 1.717 in x 19 in x 8.858 in (W x H x D) |
| Color Code NCS | S 2502-B |
| Material | steel: DC01 (1.0330), 1.0 mm |