

Adapter SC-Duplex PC, beige, ceramic MM, M, flangeless



DESCRIPTION
SC-Duplex adapter flangeless with dust caps. Quick mounting clip integrated.

030.7016

TENDER
SC-Duplex adapter multimode in acc. with IEC 61754-4. Flangeless body and integrated quick-mounting clip. Zirconia (ceramic) alignment sleeve, beige plastic housing (multimode) / UL 94 V-0, plastic dust covers. Adapter qualified in acc. with IEC 61753-1 for category U (uncontrolled environment).

- Optical specifications:
- Delta insertion loss: ≤ 0.2 dB, testing method acc. to IEC 61300-3-4
 - Mechanical specifications:
 - Mating cycles: min. 500
 - Pull-out force: min. 70 N (per connector)
 - Delta insertion loss: ≤ 0.2 dB, testing method acc. to IEC 61300-3-4
 - Mating cycles: min. 500
 - Pull-out force: min. 70 N (per connector)

TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Fiber type	Multimode (MM)
Number of connectors (A)	1
Connector type (A)	SC-Duplex
Connector color (A)	beige
Polishing plug (A)	PC
Attenuation grade IL (A)	M
Connector class	adapter
Adapter fastening method	end cap snap-in
Sleeve material	ceramic
Standard	UL Listed according to IEC 61754-4