

Adapter SC-Duplex PC, blue, ceramic SM, C, flangeless

**DESCRIPTION**  
SC-Duplex adapter flangeless with dust caps. Quick mounting clip integrated.



030.7015

**TENDER**  
SC-Duplex adapter singlemode in acc. with IEC 61754-4. Flangeless body and integrated quick-mounting clip. Zirconia (ceramic) alignment sleeve, blue plastic housing (singlemode) / UL 94 V-0, plastic dust covers. Adapter qualified in acc. with IEC 61753-1 for category U (uncontrolled environment).

- Optical specifications:
- Delta insertion loss:  $\leq 0.2$  dB, testing method acc. to IEC 61300-3-4
  - Mechanical specifications:
  - Mating cycles: min. 500
  - Pull-out force: min. 70 N (per connector)
  - Delta insertion loss:  $\leq 0.2$  dB, testing method acc. to IEC 61300-3-4
  - Mating cycles: min. 500
  - Pull-out force: min. 70 N (per connector)

**TECHNICAL DATA**

DESCRIPTION	VALUE / VALUE RANGE
Fiber type	Singlemode (SM)
Number of connectors (A)	1
Connector type (A)	SC-Duplex
Connector color (A)	blue
Polishing plug (A)	PC
Attenuation grade IL (A)	C
Connector class	adapter
Adapter fastening method	end cap snap-in
Sleeve material	ceramic
Standard	UL Listed according to IEC 61754-4