



### Overview

Presentasjon	Tall enclosure with 48U spaces for additional equipment. Compact width to optimize data center space. For low to medium density server and networking applications.
Leveringstid	Usually in Stock

### General

Inkludert utstyr	Baying hardware Key(S) Keyed-alike doors and side panels Leveling feet Mounting hardware Pre-installed casters Side panels
------------------	--

### Physical

Maximum mounting depth	91,49 cm
Number of rack unit	48U
Minimum mounting depth	19,1 cm
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Farge	Sort
Dybde	107 cm
Rack width	19"
Høyde	225,8 cm
Vekt	138,23 kg
Permanent tillatt belastning	1020,58 Kg dynamic 1700,97 kg statisk
Bredde	60 cm

### Conformance

Standarder	UL 2416 UL 60950-1 EIA-310E
------------	-----------------------------------

Informasjonen som gis i denne dokumentasjonen inneholder generelle beskrivelser og/eller tekniske egenskaper av yreisen til produktene i dokumentet. Denne dokumentasjonen er ikke ment som en erstatning for, og må ikke brukes til å bestemme egnethet eller påliteligheten til disse produktene for spesifikke brukerapplikasjoner. Enhver bruker eller integrator er ansvarlig for å utføre egnethet og fullstendig risikovurdering, analyse og testing av produktene med hensyn til aktuell bruk. Verken Schneider Electric Industries SAS eller noen av deres datterselskaper skal være ansvarlig for misbruk av informasjonen som finnes her.

## Packing Units

Forpakning 1 vekt	157,68 kg
Forpakning 1 høyde	238,5 cm
Forpakning 1 bredde	75,2 cm
Forpakning 1 lengde	115,6 cm
Antall enheter forpakning 3	1

## Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	<a href="#">REACH-erklæring</a>
REACH fri for SVHC	Ja
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet) <a href="#">EU RoHS-erklæring</a>
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	<a href="#">Ja</a>
Take-back	Take-back program available

## Contractual warranty

Garanti	5 year repair or replace
---------	--------------------------